Use the front controller as index file. It serves as a fallback solution when # every other rewrite/redirect fails (e.g. in an aliased environment without # mod_rewrite). Additionally, this reduces the matching process for the # start page (path "/") because otherwise Apache will apply the rewriting rules # to each configured DirectoryIndex file (e.g. index.php, index.html, index.pl). #DirectoryIndex app.php

DirectoryIndex app_dev.php app.php

<IfModule mod_rewrite.c> RewriteEngine On

> # Determine the RewriteBase automatically and set it as environment variable. # If you are using Apache aliases to do mass virtual hosting or installed the # project in a subdirectory, the base path will be prepended to allow proper # resolution of the app.php file and to redirect to the correct URI. It will # work in environments without path prefix as well, providing a safe, one-size # fits all solution. But as you do not need it in this case, you can comment # the following 2 lines to eliminate the overhead. RewriteCond %(REQUEST_URI):: \$1 ^(/.+)/(.*)::\2\$ RewriteRule ^(.*) - [E=BASE: %1]

Sets the HTTP_AUTHORIZATION header removed by apache
RewriteCond %(HTTP: Authorization) .
RewriteRule .* - [E=HTTP_AUTHORIZATION: %(HTTP: Authorization)]

```
# Redirect to URI without front controller to prevent duplicate content
# (with and without `/app.php`). Only do this redirect on the initial
# rewrite by Apache and not on subsequent cycles. Otherwise we would get an
# endless redirect loop (request -> rewrite to front controller ->
# redirect -> request -> ...).
# So in case you get a "too many redirects" error or you always get redirected
# to the start page because your Apache does not expose the REDIRECT_STATUS
# environment variable, you have 2 choices:
# - disable this feature by commenting the following 2 lines or
# - use Apache >= 2.3.9 and replace all L flags by END flags and remove the
# following RewriteCond (best solution)
RewriteCond %(ENV: REDIRECT_STATUS) ^$
RewriteRule ^app\.php(/(.*)|$) %(ENV: BASE)/$2 [R=301,L]
```

If the requested filename exists, simply serve it. # Us as in most to let Oscabe serve files and set dimension # we only want to let Hpache serve files and not directories. RewriteCond %(REQUEST_FILENAME) -f RewriteRule .? - [L]

When mod_rewrite is not available, we instruct a temporary redirect of # the start page to the front controller explicitly so that the website # and the generated links can still be used. RedirectMatch 302 ^/\$ /app.php/ # RedirectTemp cannot be used instead </IfModule> </IfModule>