

```
Options +FollowSymLinks +ExecCGI
```

```
<IfModule mod_rewrite.c>
```

```
    RewriteEngine On
```

```
    # uncomment the following line, if you are having trouble  
    # getting no_script_name to work  
    # RewriteBase /
```

```
    # we skip all files with .something  
    #RewriteCond %{REQUEST_URI} \.+$  
    #RewriteCond %{REQUEST_URI} !\.html$  
    #RewriteRule .* - [L]
```

```
    # we check if the .html version is here (caching)
```

```
    RewriteRule ^$ index.html [QSA]  
    RewriteRule ^([\^.]*)$ $1.html [QSA]  
    RewriteCond %{REQUEST_FILENAME} !-f
```

```
    # no, so we redirect to our front web controller
```

```
    RewriteRule ^(.*)$ index.php [QSA,L]
```

```
</IfModule>
```

```
# -----  
# security header  
# -----
```

```
<ifModule mod_headers.c>
```

```
    # frame protection (https://developer.mozilla.org/en-US/docs/HTTP/X-Frame-Options)  
    Header set X-Frame-Options SAMEORIGIN
```

```
    # XSS protection for ie
```

```
    Header set X-XSS-Protection "1; mode=block"
```

```
    # man in the middle protection
```

```
(http://fr.wikipedia.org/wiki/HTTP\_Strict\_Transport\_Security)
```

```
    Header set Strict-Transport-Security "max-age=2592000"
```

```
</ifModule>
```

```
# -----  
# ET-----
```

```

# ctag removal
# -----
<ifModule mod_headers.c>
  Header unset ETag

  # bug symfony qui inclut toujours ces headers
  Header unset Expires
  Header unset Pragma
</ifModule>

FileETag None

# -----
# Gzip compression
# -----
<IfModule mod_deflate.c>
  # Force deflate for mangled headers developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-
  beyond-gzipping/
  <IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
      SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$
      ^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
      RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
    </IfModule>
  </IfModule>

  # Compress all output labeled with one of the following MIME-types
  # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
  # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines as
  # `AddOutputFilterByType` is still in the core directives)
  <IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
      application/javascript \
      application/json \
      application/rss+xml \
      application/vnd.ms-fontobject \
      application/x-font-ttf \
      application/xhtml+xml \
      application/xml \
      font/opentype \
      image/svg+xml \
      .

```

```
image/x-icon \  
text/css \  
text/html \  
text/plain \  
text/x-component \  
text/xml  
</IfModule>  
</IfModule>  
  
# -----  
# Expires headers  
# -----  
# gestion du cache avancee (HTTP/1.1)  
<IfModule mod_headers.c>  
  # Media: images  
  # <FilesMatch "\\. (gif|jpeg|jpg|png)$">  
  #   Header set Cache-Control "max-age=604800, public, no-transform"  
  # </FilesMatch>  
  
  # Favicon (cannot be renamed)  
  <FilesMatch "\\. (ico)$">  
    # 1 week  
    Header set Cache-Control "max-age=604800, public, no-transform"  
  </FilesMatch>  
  
  # Webfonts  
  <FilesMatch "\\. (eot|ttf|woff|otf)$">  
    # 1 month  
    Header set Cache-Control "max-age=2592000, public, no-transform"  
  </FilesMatch>  
  
  # CSS and JavaScript  
  # <FilesMatch "\\. (js|css)$">  
  #   # 1 month  
  #   Header set Cache-Control "max-age=2592000, public, no-transform"  
  # </FilesMatch>  
  
  # cache des fichiers production css et js  
  <FilesMatch "main-prod. (js|css)$">  
    # 1 month  
    Header set Cache-Control "max-age=2592000, public, no-transform"
```

```
</FilesMatch>
```

```
<FilesMatch "(topbar-noise.jpg|explorer_fr.gif|logo-wikipixel.png)$">
```

```
  # 1 week
```

```
  Header set Cache-Control "max-age=604800, public, no-transform"
```

```
</FilesMatch>
```

```
</IfModule>
```