```apache
### SILVERSTRIPE START ###
<Files *.ss>
    Order deny,allow
    Deny from all
    Allow from 127.0.0.1
</Files>

<Files web.config>
    Order deny,allow
    Deny from all
</Files>

# This denies access to all yml files, since developers might include sensitive
# information in them. See the docs for work-arounds to serve some yaml files
<Files ~ "\.ya?ml$">
    Order allow,deny
    Deny from all
</Files>

ErrorDocument 404 /assets/error-404.html
ErrorDocument 500 /assets/error-500.html

<IfModule mod_rewrite.c>
    SetEnv HTTP_MOD_REWRITE On
    RewriteEngine On

    RewriteRule ^vendor(/|$) - [F,L,NC]
    RewriteRule silverstripe-cache(/|$) - [F,L,NC]
    RewriteRule composer\.(json|lock) - [F,L,NC]

    RewriteCond %{REQUEST_URI} ^(.*)$
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_URI} !\.php$
    RewriteRule .* framework/main.php?url=%1 [QSA]

    RewriteCond %{REQUEST_URI} ^(.*)/framework/main.php$
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteRule . %1/install.php? [R,L]

</IfModule>
### SILVERSTRIPE END ###
```