

```
<IfModule mod_headers.c>
  Header unset ETag
</IfModule>

BrowserMatch "MSIE" brokenvary=1
BrowserMatch "Mozilla/4.[0-9]{2}" brokenvary=1
BrowserMatch "Opera" !brokenvary
SetEnvIf brokenvary 1 force-no-vary

FileETag none

# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml

IndexIgnore /*
Options -Indexes
Options +FollowSymLinks

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    #mod_headers, y u no match by Content-Type?!
    <FilesMatch "\.(gif|png|jpe?g|svg|svgz|ico|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>

<IfModule mod_headers.c>
  <FilesMatch "\.(ttf|tfc|otf|eot|woff|font.css)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=Edge,chrome=1"
  <FilesMatch "\.(js|css|gif|png|jpe?g|pdf|xml|ogal|ogg|m4a|ogv|mp4|m4v|webm|svg|svgz|eot|ttf|otf|woff|ico|webp|appcache|manifest|
\
```

```
>
  Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
# tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js jsonp
AddType application/json            json

# Audio
AddType audio/ogg                   oga ogg
AddType audio/mp4                   m4a f4a f4b

# Video
AddType video/ogg                    ogv
AddType video/mp4                   mp4 m4v f4v f4p
AddType video/webm                   webm
AddType video/x-flv                  flv

# SVG
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml               svg svgz
AddEncoding gzip                    svgz

# Webfonts
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf       ttf ttc
AddType font/opentype                otf
AddType application/x-font-woff      woff

# Assorted types
AddType image/x-icon                 ico
AddType image/webp                   webp
AddType text/cache-manifest          appcache manifest
AddType text/x-component              htc
AddType application/xml              rss atom xml rdf
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
```

```
AddType application/x-xpinstall xpi
AddType application/octet-stream safariextz
AddType application/x-web-app-manifest+json webapp
AddType text/x-vcard vcf
AddType application/x-shockwave-flash swf
AddType text/vtt vtt
AddType image/webp webp
```

```
<IfModule mod_deflate.c>
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\s:
HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>
```

```
# Force deflate for mangled headers developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-be
```

```
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\s:
HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
  </IfModule>
</IfModule>
```

```
# Compress all output labeled with one of the following MIME-types
```

```
<IfModule mod_filter.c>
  AddOutputFilterByType DEFLATE application/atom+xml \
    application/javascript \
    application/json \
    application/rss+xml \
    application/vnd.ms-fontobject \
    application/x-font-ttf \
    application/xhtml+xml \
    application/xml \
    font/opentype \
    image/svg+xml \
    image/x-icon \
    text/css \
    text/html \
```

```
text/plain \
text/x-component \
text/xml
```

```
</IfModule>
```

```
</IfModule>
```

```
# -----
# gzip compression
# -----
```

```
<IfModule mod_deflate.c>
```

```
# force deflate for mangled headers developer, yahoo.com/blogs/ydn/posts/2010/12/pushing-bey
```

```
<IfModule mod_setenvif.c>
```

```
<IfModule mod_headers.c>
```

```
    SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\s,
(4,13)|-(4,13))$ HAVE_Accept-Encoding
```

```
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
```

```
</IfModule>
```

```
</IfModule>
```

```
# webfonts and svg:
```

```
<FilesMatch "\.(ttf|otf|eot|svg)$" >
```

```
    SetOutputFilter DEFLATE
```

```
</FilesMatch>
```

```
<IfModule !mod_filter.c>
```

```
    AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
```

```
    AddOutputFilterByType DEFLATE application/javascript
```

```
    AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
```

```
    AddOutputFilterByType DEFLATE application/xhtml+xml application/rss+xml application/atom+
```

```
    AddOutputFilterByType DEFLATE image/svg+xml application/vnd.ms-fontobject application/x-fc
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_expires.c>
```

```
    ExpiresActive on
```

```
    ExpiresDefault "access plus 2 month"
```

```
    ExpiresByType text/cache-manifest "access plus 0 seconds"
```

```
    ExpiresByType text/html "access plus 0 seconds"
```

```
    ExpiresByType text/xml "access plus 0 seconds"
```

```

ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType application/json "access plus 0 seconds"
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType image/x-icon "access plus 1 week"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpg "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
ExpiresByType text/x-component "access plus 1 month"
ExpiresByType font/truetype "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType text/css "access plus 2 month"
ExpiresByType application/javascript "access plus 1 year"
<IfModule mod_headers.c>
    Header append Cache-Control "public"
</IfModule>
</IfModule>
Options -MultiViews

#<IfModule mod_rewrite.c>
#
#</IfModule>

<ifModule mod_gzip.c>
    mod_gzip_on Yes
    mod_gzip_dechunk Yes
    mod_gzip_item_include file \.(html?|txt|css|js|php|pl)$
    mod_gzip_item_include handler ^cgi-script$
    mod_gzip_item_include mime ^text/. *
    mod_gzip_item_include mime ^application/x-javascript.*
    mod_gzip_item_include mime ^image/. *
    mod_gzip_item_exclude rsphheader ^Content-Encoding:.*gzip.*
</ifModule>

```

```
BrowserMatch ^Mozilla/4 gzip-only-text/html
BrowserMatch ^Mozilla/4\.0[678] no-gzip
BrowserMatch \bMSIE !no-gzip !gzip-only-text/html
BrowserMatch \bMSIE[E] !no-gzip !gzip-only-text/html
SetEnvIfNoCase Request_URI \.(?:gif|jpe?g|png)$ no-gzip
Header append Vary User-Agent env=!dont-vary
```

```
<files .htaccess>
order allow,deny
deny from all
</files>
```

```
AddOutputFilterByType DEFLATE text/plain
AddOutputFilterByType DEFLATE text/xml
AddOutputFilterByType DEFLATE text/html
AddOutputFilterByType DEFLATE text/css
AddOutputFilterByType DEFLATE image/svg+xml
AddOutputFilterByType DEFLATE application/xhtml+xml
AddOutputFilterByType DEFLATE application/xml
AddOutputFilterByType DEFLATE application/rss+xml
AddOutputFilterByType DEFLATE application/atom+xml
AddOutputFilterByType DEFLATE application/x-javascript
AddOutputFilterByType DEFLATE application/x-httpd-php
AddOutputFilterByType DEFLATE application/x-httpd-fastphp
AddOutputFilterByType DEFLATE application/x-httpd-eruby
SetOutputFilter DEFLATE
SetEnvIfNoCase Request_URI \.(?:gif|jpe?g|png)$ no-gzip dont-vary
SetEnvIfNoCase Request_URI \.(?:exe|t?gz|zip|bz2|sit|rar)$ no-gzip dont-vary
SetEnvIfNoCase Request_URI \.(?:pdf|avi|mov|mp3|mp4|rm)$ no-gzip dont-vary
```

```
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteCond %{REQUEST_METHOD} ^TRACE
RewriteRule .* - [F]
#RewriteBase /www/presentation/
#RewriteCond %{HTTPS} off
#RewriteRule (.*) https://ssl6.ovh.net/~sephiroat/cohorte/%{REQUEST_URL} [QSA,L,R=301]
#RewriteCond %{HTTP_HOST} ^https://ssl6.ovh.net/~sephiroat/cohorte/$
#RewriteRule (.*) https://ssl6.ovh.net/~sephiroat/%{REQUEST_URL} [L]
```

```
# if a directory or a file exists, use it directly
#RewriteCond %{REQUEST_FILENAME} !-f
#RewriteCond %{REQUEST_FILENAME} !-d

# otherwise forward it to index.php
#RewriteRule . index.php

#RewriteCond %{HTTPS} off
# First rewrite to HTTPS:
# Don't put www. here. If it is already there it will be included, if not
# the subsequent rule will catch it.
#RewriteRule ^(.*)$ https://%{HTTP_HOST}%{REQUEST_URI} [L,R=301]

# RewriteRule "(^/)\." - [F]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond $1 !^(index\.php)
RewriteRule ^(.+)$ index.php?$1 [PT,L,QSA]

RewriteCond %{SCRIPT_FILENAME} -d [OR]
RewriteCond %{SCRIPT_FILENAME} -f
RewriteRule "(^/)\." - [F]

</IfModule>

<FilesMatch "(\\. (bak|config|sql|fla|psd|ini|log|sh|incl|swp|dist)|\\.*)">
    Order allow,deny
    Deny from all
    Satisfy All
</FilesMatch>

# Increase cookie security
<IfModule php5_module>
    php_value session.cookie_httponly true
</IfModule>

# Tmp for large data uploads
<IfModule mod_php5.c>
php_value upload_max_filesize 60M
php_value post_max_size 60M
</IfModule>
```