

```

<IfModule mod_rewrite.c>
  <IfModule mod_negotiation.c>
    Options -MultiViews
  </IfModule>

  RewriteEngine on
  RewriteBase /proys/00.skel/

  # Compatibilidad #####
  # RewriteCond %{QUERY_STRING} APP=(. *?)(\&! $)
  # RewriteRule ^(actions|api|auto|css|images|js|render)\.php$ %1?MODULE=$1 [QSA,L]
  #####

  # Debug via variable a cabeceras de la request #####
  # RewriteRule .* - [E=INFO_REQUEST_URI:%{REQUEST_URI},NE]
  # RequestHeader set INFO_REQUEST_URI "%{INFO_REQUEST_URI}e"
  # RewriteRule .* - [E=INFO_REQUEST_FILENAME:%{REQUEST_FILENAME},NE]
  # RequestHeader set INFO_REQUEST_FILENAME "%{INFO_REQUEST_FILENAME}e"
  #####

  # Comprobación recursos existentes #####
  RewriteCond %{REQUEST_FILENAME} -d [OR]
  RewriteCond %{REQUEST_FILENAME} -f
  RewriteRule .+ - [L]
  #####

  # Pages URL rewriting V2 #####
  # Barra (/) al final
  RewriteRule ^(. *[^/])$ $1/ [L,R=301,E=nocache:1] //Poner
  #RewriteRule ^(. *)/$ /$1 [L,R=301,E=nocache:1] //Quitar
  # Trataremos la URL como bloques separados por /
  # Todos los bloques hasta el último que no empiece por numero -> keywords (puede estar
o no estar)
  # El último bloque que no empiece por numero -> parametro page
  # El bloque que empiece por numero tras page -> id (puede estar o no estar)
  RewriteRule ^(?: (. *)\)?([\^0-9][\^/]*\)?(?: ([0-9][\^/]*\)?\)?$ ?page=$2&id=$3

<IfModule mod_headers.c>
  ## Set the response header if the "nocache" environment variable is set in the
RewriteRule above.
  Header always set Cache-Control "no-store, no-cache, must-revalidate, no-transform"

```

```
Header always set Cache-Control no-store, no-cache, must-revalidate env=nocache
## Set Expires too ...
Header always set Expires "Thu, 01 Jan 1970 00:00:00 GMT" env=nocache
</IfModule>
#####
</IfModule>
```