

```

<IfModule mod_rewrite.c>
    RewriteEngine On

    RewriteRule ^([0-9]+)$ error.php?code=$1 [L]

    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !^.*\.php$
    RewriteRule ^([a-z]+)$ $1.php [L]

    # Yeah, that's gone
    RewriteRule ^all-versions.php$ all-versions.php [G]
</IfModule>

# -----
# Prevent framing and XSS
# -----
<IfModule mod_headers.c>
    Header set X-Frame-Options DENY
    Header set Content-Security-Policy "frame-src http://youtube.com; script-src 'self'
'unsafe-inline' http://*.getnightingale.com; connect-src http://*.getnightingale.com
https://api.bountysource.com; default-src http://static.getnightingale.com; frame-
ancestors 'none' "
</IfModule>

<IfModule mod_mime.c>
    AddType image/x-icon          ico
</IfModule>

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>
    # Force deflate for mangled headers
    developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-beyond-gzipping/
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

```

```

    </IfModule>
</IfModule>

<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
                           application/rss+xml \
                           application/xhtml+xml \
                           application/xml \
                           text/css \
                           text/html \
                           text/plain \

</IfModule>

# -----
# Expires headers (for better cache control)
# -----

<IfModule mod_expires.c>
    ExpiresActive on

    ExpiresByType text/cache-manifest      "access plus 0 seconds"
    ExpiresByType text/html                 "access plus 0 seconds"
    ExpiresByType text/xml                  "access plus 0 seconds"
    ExpiresByType application/xml           "access plus 0 seconds"
    ExpiresByType application/json          "access plus 0 seconds"
    ExpiresByType application/rss+xml       "access plus 1 hour"
    ExpiresByType application/atom+xml      "access plus 1 hour"

</IfModule>

# -----
# ETag removal
# -----

# FileETag None is not enough for every server.
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>

# Since we're sending far-future expires, we don't need ETags for static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

```

```
# -----  
# A little more security  
# -----
```

```
# Prevent access to template files  
<FilesMatch "\.(tpl|html|xml)$">  
    Order allow,deny  
    Deny from all  
</FilesMatch>
```

```
# -----  
# Custom Errors  
# -----
```

```
ErrorDocument 500 http://getnightingale.com/500  
ErrorDocument 400 http://getnightingale.com/400  
ErrorDocument 401 http://getnightingale.com/401  
ErrorDocument 403 http://getnightingale.com/403  
ErrorDocument 404 http://getnightingale.com/404  
ErrorDocument 410 http://getnightingale.com/410
```