

[DirectoryIndex](#) index.php

```
<IfModule sapi_apache2.c>
  php_value register_globals      0
  php_value magic_quotes_gpc      0
  php_value magic_quotes_runtime  0
  php_value magic_quotes_sybase   0
  php_value arg_separator.output  "&"
  php_value default_charset       "utf-8"
  php_value session.name          "AK_SESSID"
</IfModule>
```

```
<IfModule mod_php4.c>
  php_value register_globals      0
  php_value magic_quotes_gpc      0
  php_value magic_quotes_runtime  0
  php_value magic_quotes_sybase   0
  php_value arg_separator.output  "&"
  php_value default_charset       "utf-8"
  php_value session.name          "AK_SESSID"
</IfModule>
```

```
# On some servers this directive might be needed
# Options +FollowSymLinks
```

```
# Various rewrite rules
```

```
<IfModule mod_rewrite.c>
  RewriteEngine on
```

```
# If your Akelos Framework application is accessed via an Alias directive,
# then you MUST also set the RewriteBase in this htaccess file.
#
```

```
# Example:
# Alias /myakelosapp /path/to/myakelosapp/public
# RewriteBase /framework
```

```
# If you don't want The Akelos Framework to look in certain directories,
# use the following rewrite rules so that Apache won't rewrite certain requests
#
```

```
# Example:
# RewriteCond %{REQUEST_URI} ^/static/.*$
```

```
# RewriteCond %{REQUEST_URI} /notakeios.*
# RewriteRule .* - [L]

# Rewrite URLs of the form 'index.php?ak=x':
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule ^(.*)$ index.php?ak=$1 [L,QSA]
</IfModule>

ErrorDocument 400 /public/400.html
ErrorDocument 500 /public/500.html
```