

Options -MultiViews

```
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    <FilesMatch "\.(curl|gif|ico|jpe?g|png|svgz?|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>

<IfModule mod_headers.c>
  <FilesMatch "\.(eot|otf|ttc|ttf|woff)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=edge"
  # `mod_headers` can't match based on the content-type, however, we only
  # want to send this header for HTML pages and not for the other resources
  <FilesMatch "\.(appcache|crx|css|curl|eot|gif|htc|ico|jpe?
gl|js|m4a|m4v|manifest|mp4|oex|ogal|oggl|ogv|otf|pdf|png|safariextz|svgz?
|ttf|vcf|webapp|webm|webpl|woff|xml|xpi)$">
    Header unset X-UA-Compatible
  </FilesMatch>
</IfModule>

<IfModule mod_mime.c>

  # Audio
  AddType audio/mp4          m4a f4a f4b
  AddType audio/ogg          oga ogg

  # JavaScript
  # Normalize to standard type (it's sniffed in IE anyways):
  # http://tools.ietf.org/html/rfc4329#section-7.2
  AddType application/javascript    js
  AddType application/json          json

  # ...
```

```
# video
AddType video/mp4                f4v f4p m4v mp4
AddType video/ogg                 ogv
AddType video/webm                webm
AddType video/x-flv               flv

# Web fonts
AddType application/font-woff     woff
AddType application/vnd.ms-fontobject eot

# Browsers usually ignore the font MIME types and sniff the content,
# however, Chrome shows a warning if other MIME types are used for the
# following fonts.
AddType application/x-font-ttf    ttc ttf
AddType font/opentype             otf

# Make SVGZ fonts work on iPad:
# https://twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml            svgz
AddEncoding gzip                  svgz

# Other
AddType application/octet-stream  safariextz
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpiinstall  xpi
AddType application/xml           atom rdf rss xml
AddType image/webp                webp
AddType image/x-icon              cur
AddType text/cache-manifest       appcache manifest
AddType text/vtt                  vtt
AddType text/x-component          htc
AddType text/x-vcard              vcf

</IfModule>

<ifModule mod_headers.c>
  Header unset ETag
</ifModule>
FileETag None
```

```
AddDefaultCharset utf-8
```

```
<IfModule mod_rewrite.c>
```

```
Options +FollowSymlinks
```

```
RewriteEngine On
```

```
RewriteBase /
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !\.htm
```

```
RewriteCond %{REQUEST_FILENAME} !\.html
```

```
RewriteCond %{REQUEST_FILENAME} !\.inc
```

```
RewriteCond %{REQUEST_FILENAME} !\.swf
```

```
RewriteCond %{REQUEST_FILENAME} !\.flv
```

```
RewriteCond %{REQUEST_FILENAME} !\.xml
```

```
RewriteCond %{REQUEST_FILENAME} !\.htc
```

```
RewriteCond %{REQUEST_FILENAME} !\.mp4
```

```
RewriteCond %{REQUEST_FILENAME} !\.webm
```

```
RewriteCond %{REQUEST_FILENAME} !\.ogv
```

```
RewriteCond %{REQUEST_URI} !.*\.(ico|gif|jpg|jpeg|png|js|css)
```

```
RewriteRule ^([^\?]*).* index.php?_route_=$1 [L,QSA]
```

```
</IfModule>
```

```
<IfModule mod_rewrite.c>
```

```
RewriteCond %{HTTPS} !=on
```

```
RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
```

```
RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
```

```
</IfModule>
```

```
<IfModule mod_autoindex.c>
```

```
Options -Indexes
```

```
</IfModule>
```

```
# -----
```

```
# Block access to hidden files and directories.
```

```
# This includes directories used by version control systems such as Git and SVN.
```

```
<IfModule mod_rewrite.c>
```

```

RewriteCond %{SCRIPT_FILENAME} -d [OR]
RewriteCond %{SCRIPT_FILENAME} -f
RewriteRule "^(\/)\." - [F]
</IfModule>

<FilesMatch "(\^#\.#\ \.(bak|config|dist|fla|incl|ini|log|psd|sh|sql|sw[op])|(\^)\$)">

    # Apache < 2.3
    <IfModule !mod_authz_core.c>
        Order allow,deny
        Deny from all
        Satisfy All
    </IfModule>

    # Apache ≥ 2.3
    <IfModule mod_authz_core.c>
        Require all denied
    </IfModule>

</FilesMatch>

<IfModule mod_deflate.c>

    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ymdn/posts/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Compress all output labeled with one of the following MIME-types
    # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
    # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
    # as `AddOutputFilterByType` is still in the core directives).
    <IfModule mod_filter.c>
        AddOutputFilterByType DEFLATE application/atom+xml \
            application/javascript \
            application/json \

```

```
application/rss+xml \
application/vnd.ms-fontobject \
application/x-font-ttf \
application/x-web-app-manifest+json \
application/xhtml+xml \
application/xml \
font/opentype \
image/svg+xml \
image/x-icon \
text/css \
text/html \
text/plain \
text/x-component \
text/xml
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
ExpiresDefault "access plus 1 month"
```

```
# CSS
```

```
ExpiresByType text/css "access plus 1 year"
```

```
# Data interchange
```

```
ExpiresByType application/json "access plus 0 seconds"
```

```
ExpiresByType application/xml "access plus 0 seconds"
```

```
ExpiresByType text/xml "access plus 0 seconds"
```

```
# Favicon (cannot be renamed!) and cursor images
```

```
ExpiresByType image/x-icon "access plus 1 week"
```

```
# HTML components (HTCs)
```

```
ExpiresByType text/x-component "access plus 1 month"
```

```
# HTML
```

```
ExpiresByType text/html "access plus 0 seconds"
```

```
# JavaScript
```

ExpiresByType application/javascript "access plus 1 year"

Manifest files

ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"

ExpiresByType text/cache-manifest "access plus 0 seconds"

Media

ExpiresByType audio/ogg "access plus 1 month"

ExpiresByType image/gif "access plus 1 month"

ExpiresByType image/jpeg "access plus 1 month"

ExpiresByType image/png "access plus 1 month"

ExpiresByType video/mp4 "access plus 1 month"

ExpiresByType video/ogg "access plus 1 month"

ExpiresByType video/webm "access plus 1 month"

Web feeds

ExpiresByType application/atom+xml "access plus 1 hour"

ExpiresByType application/rss+xml "access plus 1 hour"

Web fonts

ExpiresByType application/font-woff "access plus 1 month"

ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

ExpiresByType application/x-font-ttf "access plus 1 month"

ExpiresByType font/opentype "access plus 1 month"

ExpiresByType image/svg+xml "access plus 1 month"

</IfModule>