

```
#Set environment
SetEnv KOHANA_ENV "PRODUCTION"
#SetEnv KOHANA_ENV "DEVELOPMENT"

# Turn on URL rewriting
Options +FollowSymLinks
Options -Indexes
RewriteEngine on
RewriteBase /

# Installation directory
RewriteBase /tcmaker/portfolio

# Protect hidden files from being viewed
<Files .*>
    Order Deny,Allow
    Deny From All
</Files>

# Protect application and system files from being viewed
RewriteRule ^(?: application| modules| system)\b.* index.php/$0 [L]

# Allow any files or directories that exist to be displayed directly
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d

# Rewrite all other URLs to index.php/URL
RewriteRule ^(.*)$ index.php?/$1 [PT,L]

# -----
# Webfont access
# -----

# allow access from all domains for webfonts
# alternatively you could only whitelist
# your subdomains like "sub.domain.com"

<FilesMatch "\.(ttf|otf|eot|woff|font. css)$">
    <IfModule mod_headers.c>
        Header set Access-Control-Allow-Origin "*"
    </IfModule>
</FilesMatch>
```

```
</ITModule>
```

```
</FilesMatch>
```

```
# -----  
# Proper MIME type for all files  
# -----
```

```
# audio
```

```
AddType audio/ogg oga ogg
```

```
# video
```

```
AddType video/ogg ogv
```

```
AddType video/mp4 mp4
```

```
AddType video/webm webm
```

```
# Proper svg serving. Required for svg webfonts on iPad
```

```
# twitter.com/FontSquirrel/status/14855840545
```

```
AddType image/svg+xml svg svgz
```

```
AddEncoding gzip svgz
```

```
# webfonts
```

```
AddType application/vnd.ms-fontobject eot
```

```
AddType font/truetype ttf
```

```
AddType font/opentype otf
```

```
AddType application/x-font-woff woff
```

```
# assorted types
```

```
AddType image/x-icon ico
```

```
AddType image/webp webp
```

```
AddType text/cache-manifest appcache manifest
```

```
AddType text/x-component htc
```

```
AddType application/x-chrome-extension crx
```

```
AddType application/x-xpinstall xpi
```

```
AddType application/octet-stream safariextz
```

```
# -----  
# UTF-8 encoding  
# -----
```

```
# use utf-8 encoding for anything served text/plain or text/html
```

```
AddDefaultCharset utf-8
```

force utf-8 for a number of file formats

AddCharset utf-8 .html .css .js .xml .json .rss