

```
# See https://github.com/h5bp/html5-boilerplate/blob/master/dist/.htaccess
# and https://gist.github.com/chriso/874000 for more information
# about some of these directives.
```

```
# Everything is UTF-8
```

```
AddDefaultCharset utf-8
```

```
AddCharset utf-8 .atom \
```

```
    .bbaw \
```

```
    .css \
```

```
    .geojson \
```

```
    .js \
```

```
    .json \
```

```
    .jsonld \
```

```
    .manifest \
```

```
    .rdf \
```

```
    .rss \
```

```
    .topojson \
```

```
    .vtt \
```

```
    .webapp \
```

```
    .webmanifest \
```

```
    .xloc \
```

```
    .xml
```

```
# No directory listings (for security)
```

```
<IfModule mod_autoindex.c>
```

```
    Options -Indexes
```

```
</IfModule>
```

```
# Avoid rewriting issues
```

```
Options -MultiViews
```

```
# Alter HTTP headers for improved security
```

```
Header set X-Content-Type-Options "nosniff"
```

```
Header set X-XSS-Protection "1; mode=block"
```

```
Header unset X-Powered-By
```

```
# Hide Apache somewhat (see html5boilerplate for details)
```

```
ServerSignature Off
```

```
# GZip settings from html5boilerplate
```

```
<IfModule mod_deflate.c>
```

```

<IfModule mod_deflate.c>
SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\s*,?\s*)+| [X"-]{4,13}$ HAVE_Accept-Encoding
RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
AddOutputFilterByType DEFLATE "application/atom+xml" \
    "application/javascript" \
    "application/json" \
    "application/ld+json" \
    "application/manifest+json" \
    "application/rdf+xml" \
    "application/rss+xml" \
    "application/schema+json" \
    "application/vnd.geo+json" \
    "application/vnd.ms-fontobject" \
    "application/x-font-ttf" \
    "application/x-javascript" \
    "application/x-web-app-manifest+json" \
    "application/xhtml+xml" \
    "application/xml" \
    "font/eot" \
    "font/opentype" \
    "image/bmp" \
    "image/svg+xml" \
    "image/vnd.microsoft.icon" \
    "image/x-icon" \
    "text/cache-manifest" \
    "text/css" \
    "text/html" \
    "text/javascript" \
    "text/plain" \
    "text/vcard" \
    "text/vnd.rim.location.xloc" \
    "text/vtt" \
    "text/x-component" \
    "text/x-cross-domain-policy" \
    "text/xml"

</IfModule>

# Don't let proxies create problems
Header merge Cache-Control "no-transform"

```

```
RewriteEngine On
# Rewrite cache-busting urls
RewriteRule ^(.*)\.hash-.*?\.(.*)$ $1.$2 [PT]
# Except for specific (whitelisted) files, rewrite everything to index.php
# for appropriate routing.
RewriteRule !^(styles\.css|client\.js|lib\|.!\img\|.!\docs\|.!\robots\.txt)$ index.php

# Misc. caching settings
FileETag All
Header merge Cache-Control "private"

# For ordinary (noncachebusted) files, set a very short expiration time.
ExpiresActive on
ExpiresDefault "access plus 0 seconds"

# Because we use cachebusting URLs, we can set "expires"
# very far in the future.
ExpiresByType text/css "access plus 1 year"
ExpiresByType application/javascript "access plus 1 year"
ExpiresByType application/x-javascript "access plus 1 year"
ExpiresByType text/javascript "access plus 1 year"
```