

```
# =====  
# Cross-origin web fonts  
# =====
```

```
# Allow cross-origin access to web fonts.
```

```
<IfModule mod_headers.c>  
  <FilesMatch "\.(eot|otf|ttf|woff2?)$">  
    Header set Access-Control-Allow-Origin "*"   
  </FilesMatch>  
</IfModule>
```

```
# =====  
# Media types  
# =====
```

```
<IfModule mod_mime.c>  
  AddType application/json json map topojson  
  AddType application/ld+json jsonld  
  AddType application/vnd.geo+json geojson  
  AddType application/xml atom rdf rss xml  
  AddType application/javascript js  
  AddType application/x-web-app-manifest+json webapp  
  AddType text/cache-manifest appcache manifest  
  AddType audio/mp4 f4a f4b m4a  
  AddType audio/ogg oga ogg opus  
  AddType image/bmp bmp  
  AddType image/svg+xml svg svgz  
  AddType image/webp webp  
  AddType video/mp4 f4v f4p m4v mp4  
  AddType video/ogg ogv  
  AddType video/webm webm  
  AddType video/x-flv flv  
  AddType image/x-icon cur ico  
  AddType application/font-woff woff  
  AddType application/font-woff2 woff2  
  AddType application/vnd.ms-fontobject eot  
  AddType application/x-font-ttf ttc ttf  
  AddType font/opentype otf  
  AddType application/octet-stream safariextz  
  AddType application/vnd.ms-fontobject eot
```

```
AddType application/x-eb-appworld          bbaw
AddType application/x-chrome-extension      crx
AddType application/x-opera-extension       oex
AddType application/x-xpinstall            xpi
AddType text/vcard                         vcard vcf
AddType text/vnd.rim.location.xloc         xloc
AddType text/vtt                           vtt
AddType text/x-component                   htc
```

```
</IfModule>
```

```
# =====
# Character encodings
# =====
```

```
AddDefaultCharset utf-8
```

```
<IfModule mod_mime.c>
```

```
AddCharset utf-8 .atom \
               .bbaw \
               .css \
               .geojson \
               .js \
               .json \
               .jsonld \
               .rdf \
               .rss \
               .topojson \
               .vtt \
               .webapp \
               .xloc \
               .xml
```

```
</IfModule>
```

```
# =====
# non-WWW to WWW
# =====
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine On
RewriteCond %{HTTPS} !=on
RewriteCond %{HTTP_HOST} !^www\. [NC]
RewriteRule ^(.*)$ http://www%1 [R=301,L]
```

```

RewriteCond %{SERVER_ADDR} !=127.0.0.1
RewriteCond %{SERVER_ADDR} !=:1
RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
</IfModule>

# =====
# File access
# =====

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# =====
# Compression
# =====

<IfModule mod_deflate.c>
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)l ~(15)l -(15))$
            ^((gzip|deflate)\s*, ?\s*)+ [X"-]{4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>
</IfModule>
<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE "application/atom+xml" \
        "application/javascript" \
        "application/json" \
        "application/ld+json" \
        "application/manifest+json" \
        "application/rdf+xml" \
        "application/rss+xml" \
        "application/schema+json" \
        "application/vnd.geo+json" \
        "application/vnd.ms-fontobject" \
        "application/x-font-ttf" \
        "application/x-javascript" \
        "application/x-web-app-manifest+json" \
        "application/xhtml+xml" \
        "application/xml" \
        ..

```

```
"font/eot" \  
"font/opentype" \  
"image/bmp" \  
"image/svg+xml" \  
"image/vnd.microsoft.icon" \  
"image/x-icon" \  
"text/cache-manifest" \  
"text/css" \  
"text/html" \  
"text/javascript" \  
"text/plain" \  
"text/vcard" \  
"text/vnd.rim.location.xloc" \  
"text/vtt" \  
"text/x-component" \  
"text/x-cross-domain-policy" \  
"text/xml"
```

```
</IfModule>
```

```
<IfModule mod_mime.c>
```

```
    AddEncoding gzip          svgz
```

```
</IfModule>
```

```
</IfModule>
```

```
# =====  
#   ETags  
# =====
```

```
<IfModule mod_headers.c>
```

```
    Header unset ETag
```

```
</IfModule>
```

```
FileETag None
```

```
# =====  
#   Expires headers  
# =====
```

```
<IfModule mod_expires.c>
```

```
    ExpiresActive on
```

```
    ExpiresDefault             "access plus 1 month"
```

```
    ExpiresByType text/css    "access plus 1 year"
```

ExpiresByType	application/atom+xml	"access plus 1 hour"
ExpiresByType	application/rdf+xml	"access plus 1 hour"
ExpiresByType	application/rss+xml	"access plus 1 hour"
ExpiresByType	application/json	"access plus 0 seconds"
ExpiresByType	application/ld+json	"access plus 0 seconds"
ExpiresByType	application/schema+json	"access plus 0 seconds"
ExpiresByType	application/vnd.geo+json	"access plus 0 seconds"
ExpiresByType	application/xml	"access plus 0 seconds"
ExpiresByType	text/xml	"access plus 0 seconds"
ExpiresByType	image/vnd.microsoft.icon	"access plus 1 week"
ExpiresByType	image/x-icon	"access plus 1 week"
ExpiresByType	text/html	"access plus 0 seconds"
ExpiresByType	application/javascript	"access plus 1 year"
ExpiresByType	application/x-javascript	"access plus 1 year"
ExpiresByType	text/javascript	"access plus 1 year"
ExpiresByType	application/manifest+json	"access plus 1 year"
ExpiresByType	application/x-web-app-manifest+json	"access plus 0 seconds"
ExpiresByType	text/cache-manifest	"access plus 0 seconds"
ExpiresByType	audio/ogg	"access plus 1 month"
ExpiresByType	image/bmp	"access plus 1 month"
ExpiresByType	image/gif	"access plus 1 month"
ExpiresByType	image/jpeg	"access plus 1 month"
ExpiresByType	image/png	"access plus 1 month"
ExpiresByType	image/svg+xml	"access plus 1 month"
ExpiresByType	video/mp4	"access plus 1 month"
ExpiresByType	video/ogg	"access plus 1 month"
ExpiresByType	video/webm	"access plus 1 month"
ExpiresByType	application/vnd.ms-fontobject	"access plus 1 month"
ExpiresByType	font/eot	"access plus 1 month"
ExpiresByType	font/opentype	"access plus 1 month"
ExpiresByType	application/x-font-ttf	"access plus 1 month"
ExpiresByType	application/font-woff	"access plus 1 month"
ExpiresByType	application/x-font-woff	"access plus 1 month"
ExpiresByType	font/woff	"access plus 1 month"
ExpiresByType	application/font-woff2	"access plus 1 month"
ExpiresByType	text/x-cross-domain-policy	"access plus 1 week"

</IfModule>