

```

Options +FollowSymLinks
RewriteEngine On
RewriteBase /ojs
#RewriteRule ^oai - [L,NC]
#RewriteRule ^oai\.html$ oai [NC]
RewriteRule ^oai\.html$ /ojs/oai
RewriteRule ^oai$ /ojs/index.php?journal=Relaciones_Internacionales&page=oai [QSA,L]

# -----
# | Expires headers |
# -----

# The following expires headers are set pretty far in the future. If you
# don't control versioning with filename-based cache busting, consider
# lowering the cache time for resources such as style sheets and JavaScript
# files to something like one week.

<IfModule mod_expires.c>

    ExpiresActive on
    ExpiresDefault "access plus 1 month"

    # CSS
    ExpiresByType text/css "access plus 1 week"

    # Data interchange
    ExpiresByType application/json "access plus 0 seconds"
    ExpiresByType application/ld+json "access plus 0 seconds"
    ExpiresByType application/xml "access plus 0 seconds"
    ExpiresByType text/xml "access plus 0 seconds"

    # Favicon (cannot be renamed!) and cursor images
    ExpiresByType image/x-icon "access plus 1 week"

    # HTML components (HTCs)
    ExpiresByType text/x-component "access plus 1 month"

    # HTML
    ExpiresByType text/html "access plus 0 seconds"

    # JavaScript

```

```

# Javascript
ExpiresByType application/javascript "access plus 1 week"

# Manifest files
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"

# Media
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# Web feeds
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"

# Web fonts
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"

</IfModule>

# -----
# | Compression |
# -----

<IfModule mod_deflate.c>

    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ymdn/posts/2010/12/pushing-beyond-gzipping
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*,\s*\?(s*))\+ [X"-]{4,13}$ HAVE_Accept-Encoding

```

```

    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
</IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).
<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
        application/javascript \
        application/json \
        application/ld+json \
        application/rss+xml \
        application/vnd.ms-fontobject \
        application/x-font-ttf \
        application/x-web-app-manifest+json \
        application/xhtml+xml \
        application/xml \
        font/opentype \
        image/svg+xml \
        image/x-icon \
        text/css \
        text/html \
        text/plain \
        text/x-component \
        text/xml

</IfModule>

</IfModule>

# Do not rewrite anything that starts with index/
#RewriteRule ^admin(.*)$ ojs/index.php/index/admin$1 [L]

#PDFS
RewriteCond %{THE_REQUEST} /ojs/index\.php\?
RewriteCond %{REQUEST_METHOD} !POST$
RewriteCond %{QUERY_STRING} ^journal=(\w+)&page=article&op=download&path\%5B\%5D=
(\w+)&path\%5B\%5D=(\w+)$ [NC]
RewriteRule (.*) http://www.relacionesinternacionales.info/ojs/%2/article/download/%3/%4.pdf
[QSA,R=301]

```

```

#RewriteCond %{REQUEST_METHOD} !POST$
#RewriteRule ^article/viewFile/([^/]*)/([^/]*)\.html$ /ojs/article/view/$1/$2.html [R=301]
RewriteCond %{REQUEST_METHOD} !POST$
RewriteRule ^article/download/([^/]*)/([^/]*)\.html$ /ojs/article/download/$1/$2.pdf
[QSA, L, R=301]
RewriteCond %{REQUEST_METHOD} !POST$
RewriteRule ^article/download/([^/]*)/([^/]*)\.pdf$ /ojs/index.php?
journal=Relaciones_Internacionales&page=article&op=download&path[]= $1 &path[]=$2 [QSA, L]

#1. PAGINAS TERCER NIVEL
RewriteCond %{THE_REQUEST} /ojs/index\.php\?
RewriteCond %{REQUEST_METHOD} !POST$
RewriteCond %{QUERY_STRING} ^journal=(\w+) &page=(\w+) &op=(\w+) &path\[]=(\w+) &path\[]=(\w+) $
[OR]
RewriteCond %{QUERY_STRING} ^journal=(\w+) &page=(\w+) &op=(\w+) &path\%5B\%5D=
(\w+) &path\%5B\%5D=(\w+) $ [NC]
RewriteRule (.*) http://www.relacionesinternacionales.info/ojs/%2/%3/%4/%5.html [QSA, L, R=301]

#2. ABSTRACTS Y NUMEROS
RewriteCond %{THE_REQUEST} /ojs/index\.php\?
RewriteCond %{REQUEST_METHOD} !POST$
RewriteCond %{QUERY_STRING} ^journal=(\w+) &page=(\w+) &op=(\w+) &path\[]=(\w+) $ [OR]
RewriteCond %{QUERY_STRING} ^journal=(\w+) &page=(\w+) &op=(\w+) &path\%5B\%5D=(\w+) $ [OR]
RewriteCond %{QUERY_STRING} ^journal=(\w+) &page=(\w+) &op=(\w+) &subject=(\w+) [NC]
RewriteRule (.*) http://www.relacionesinternacionales.info/ojs/%2/%3/%4.html [QSA, L, R=301]

#3. PAGINAS SEGUNDO NIVEL
RewriteCond %{THE_REQUEST} /ojs/index\.php\?
RewriteCond %{REQUEST_METHOD} !POST$
RewriteCond %{QUERY_STRING} journal=(\w+) &page=(\w+) &op=(\w+) $ [NC]
RewriteRule (.*) http://www.relacionesinternacionales.info/ojs/%2/%3.html [QSA, L, R=301]

#4. PAGINAS PRIMER NIVEL
RewriteCond %{THE_REQUEST} /ojs/index\.php\?
RewriteCond %{REQUEST_METHOD} !POST$
RewriteCond %{QUERY_STRING} journal=(\w+) &page=(\w+) $ [NC]
RewriteRule (.*) http://www.relacionesinternacionales.info/ojs/%2.html [QSA, L, R=301]

#5. PREESCRITURA GENERAL
#RewriteRule ^index/([^/]*)\.html$ /ojs/index.php?journal=index&page=$1 [QSA, L]

```

```
RewriteCond %{REQUEST_METHOD} !POST$
RewriteRule ^index/([^/]*)/([^/]*)\.html$ /ojs/index.php?journal=index&page=$1 &op=$2 [QSA, L]
RewriteCond %{REQUEST_METHOD} !POST$
RewriteRule ^search/advancedResults/([^/]*)\.html$ /ojs/index.php?
journal=Relaciones_Internacionales&page=search&op=advancedResults&subject=$1 [QSA, L]
RewriteCond %{REQUEST_METHOD} !POST$
RewriteRule ^([^/]*)/([^/]*)/([^/]*)/([^/]*)\.html$ /ojs/index.php?
journal=Relaciones_Internacionales&page=$1 &op=$2&path[]=$3&path[]=$4 [QSA, L]
RewriteCond %{REQUEST_METHOD} !POST$
RewriteRule ^([^/]*)/([^/]*)/([^/]*)\.html$ /ojs/index.php?
journal=Relaciones_Internacionales&page=$1 &op=$2&path[]=$3 [QSA, L]
RewriteCond %{REQUEST_METHOD} !POST$
RewriteRule ^([^/]*)/([^/]*)\.html$ /ojs/index.php?
journal=Relaciones_Internacionales&page=$1 &op=$2 [QSA, L]
RewriteCond %{REQUEST_METHOD} !POST$
RewriteRule ^([^/]*)\.html$ /ojs/index.php?journal=Relaciones_Internacionales&page=$1 [QSA, L]
```