

```
Options +FollowSymLinks +ExecCGI
AddType text/x-component .htc
AddType text/javascript .jsgz
AddType text/css .cssgz
AddEncoding x-gzip .jsgz .cssgz
```

```
<IfModule mod_rewrite.c>
```

```
    RewriteEngine On
```

```
    # uncomment the following line, if you are having trouble
    # getting no_script_name to work
```

```
    RewriteBase /
```

```
    # Standby mechanism to prevent race conditions during deployment.
    # apostrophe: deploy looks for these rules and
    # comments and uncomments them at appropriate times. Please
    # do NOT modify them if you want this feature to work.
```

```
#
```

```
# RewriteCond %{REQUEST_URI} !^/apostrophe-standby
# RewriteRule ^.*$ /apostrophe-standby/index.html [L]
```

```
##### BEGIN special handling for the media module's cached scaled images
# If it exists, just deliver it
```

```
# We need to repeat the standby check because of the redirect issue in Apache 2.2
```

```
# RewriteCond %{REQUEST_URI} !^/apostrophe-standby
RewriteCond %{REQUEST_URI} ^/uploads/media_items/.+$
RewriteCond %{REQUEST_FILENAME} -f
RewriteRule .* - [L]
```

```
# If it doesn't exist, render it via the front end controller
```

```
# RewriteCond %{REQUEST_URI} !^/apostrophe-standby
RewriteCond %{REQUEST_URI} ^/uploads/media_items/.+$
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^(.*)$ index.php [QSA,L]
```

```
##### END special handling for the media module's cached scaled images
```

```
# we skip all files with .something
```

```
# RewriteCond %{REQUEST_URI} !^/apostrophe-standby
RewriteCond %{REQUEST_URI} \.+$
RewriteCond %{REQUEST_URI} !\.html$
RewriteRule .* - [L]
```

```
# we check if the .html version is here (caching)
# RewriteCond %{REQUEST_URI} !^/apostrophe-standby
RewriteRule ^$ index.html [QSA]
RewriteRule ^([^.]+)$ $1.html [QSA]
RewriteCond %{REQUEST_FILENAME} !-f

# no, so we redirect to our front web controller
# RewriteCond %{REQUEST_URI} !^/apostrophe-standby
RewriteRule ^(.*)$ index.php [QSA,L]
</IfModule>

# Apostrophe currently requires this, but don't try to force it on
# environments that don't have php_value (those environments can
# still do it in php.ini if they have altered the default)
<IfModule mod_php5.c>
    php_value arg_separator.output "&"
</IfModule>
```