

```
#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|themel|tpl(\. php)?|xmp|svn-
base)$|^(\code-style\..|Entries.*|Repository|Root|Tag|Template|all-
wcprops|entries|format)$">
    Order allow,deny
</FilesMatch>

AddType x-mapp-php5 .php

#Next line added 20101118 based on http://drupal.org/getting-started/clean-urls
RewriteBase /

#Next line added 20101118 based on
http://www.anelloconsulting.com/case_study_increasing_yslow_score_30_points_less_one_hour
FileETag none

# Added 20101118 - http://davidherron.com/content/reducing-bandwidth-use-decreasing-page-
load-times-better-drupal-user-experience # <IfModule mod_deflate.c>
# AddOutputFilterByType DEFLATE text/html text/plain text/xml text/css text/javascript
application/x-javascript # # application/javascript
# </IfModule>

<IfModule mod_deflate.c>
    AddOutputFilterByType DEFLATE text/plain
    AddOutputFilterByType DEFLATE text/html
    AddOutputFilterByType DEFLATE text/xml
    AddOutputFilterByType DEFLATE text/css
    AddOutputFilterByType DEFLATE image/svg+xml
    AddOutputFilterByType DEFLATE image/x-icon
    AddOutputFilterByType DEFLATE application/xml
    AddOutputFilterByType DEFLATE application/xhtml+xml
    AddOutputFilterByType DEFLATE application/rss+xml
    AddOutputFilterByType DEFLATE application/javascript
    AddOutputFilterByType DEFLATE application/x-javascript
    AddOutputFilterByType DEFLATE application/x-javascript

```

```
AddOutputFilterByType DEFLATE application/x-httpd-php
AddOutputFilterByType DEFLATE application/x-httpd-fastphp
AddOutputFilterByType DEFLATE application/x-httpd-eruby
```

```
DeflateCompressionLevel 9
```

```
# Netscape 4.X has some problems
```

```
BrowserMatch ^Mozilla/4 gzip-only-text/html
```

```
# Netscape 4.06-4.08 have some more problems
```

```
BrowserMatch ^Mozilla/4\.0[678] no-gzip
```

```
# MSIE masquerades as Netscape, but it is fine
```

```
BrowserMatch \bMSIE !no-gzip !gzip-only-text/html
```

```
# Setup custom deflate log
```

```
# DeflateFilterNote Input instream
```

```
# DeflateFilterNote Output outstream
```

```
# DeflateFilterNote Ratio ratio
```

```
#
```

```
# LogFormat '"%r" %(outstream)n/%(instream)n (%(ratio)n%%)' deflate
```

```
# Example of log file (add to vhosts)
```

```
# CustomLog logs/deflate_log DEFLATE
```

```
</IfModule>
```

```
# Don't show directory listings for URLs which map to a directory.
```

```
Options -Indexes
```

```
# Follow symbolic links in this directory.
```

```
Options +FollowSymLinks
```

```
# Make Drupal handle any 404 errors.
```

```
ErrorDocument 404 /index.php
```

```
# Force simple error message for requests for non-existent favicon.ico.
```

```
<Files favicon.ico>
```

```
# There is no end quote below, for compatibility with Apache 1.3.
```

```
ErrorDocument 404 "The requested file favicon.ico was not found.
```

```
</Files>
```

```
# Set the default handler.
```

```
Handler .php .php5 .php7
```

[DirectoryIndex](#) index.php

```
# Override PHP settings. More in sites/default/settings.php  
# but the following cannot be changed at runtime.
```

```
# PHP 4, Apache 1.
```

```
<IfModule mod_php4.c>  
  php_value magic_quotes_gpc          0  
  php_value register_globals          0  
  php_value session.auto_start       0  
  php_value mbstring.http_input       pass  
  php_value mbstring.http_output      pass  
  php_value mbstring.encoding_translation 0  
</IfModule>
```

```
# PHP 4, Apache 2.
```

```
<IfModule sapi_apache2.c>  
  php_value magic_quotes_gpc          0  
  php_value register_globals          0  
  php_value session.auto_start       0  
  php_value mbstring.http_input       pass  
  php_value mbstring.http_output      pass  
  php_value mbstring.encoding_translation 0  
</IfModule>
```

```
# PHP 5, Apache 1 and 2.
```

```
<IfModule mod_php5.c>  
  php_value magic_quotes_gpc          0  
  php_value register_globals          0  
  php_value session.auto_start       0  
  php_value mbstring.http_input       pass  
  php_value mbstring.http_output      pass  
  php_value mbstring.encoding_translation 0  
</IfModule>
```

```
# Requires mod_expires to be enabled.
```

```
<IfModule mod_expires.c>
```

```
  # Enable expirations.
```

```
  ExpiresActive On
```

```
  # Cache all files for 2 weeks after access (A).
```

ExpiresDefault A1209600

<FilesMatch \.php\$>

Do not allow PHP scripts to be cached unless they explicitly send cache headers themselves. Otherwise all scripts would have to overwrite the headers set by mod_expires if they want another caching behavior. This may fail if an error occurs early in the bootstrap process, and it may cause problems if a non-Drupal PHP file is installed in a subdirectory.

ExpiresActive Off

</FilesMatch>

</IfModule>

Various rewrite rules.

<IfModule mod_rewrite.c>

RewriteEngine on

If your site can be accessed both with and without the 'www.' prefix, you can use one of the following settings to redirect users to your preferred URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:

#

To redirect all users to access the site WITH the 'www.' prefix, (http://example.com/... will be redirected to http://www.example.com/...) adapt and uncomment the following:

RewriteCond %{HTTP_HOST} ^example\.com\$ [NC]

RewriteRule ^(.)\$ http://www.example.com/\$1 [L,R=301]*

#

To redirect all users to access the site WITHOUT the 'www.' prefix, (http://www.example.com/... will be redirected to http://example.com/...) uncomment and adapt the following:

RewriteCond %{HTTP_HOST} ^www\.example\.com\$ [NC]

RewriteRule ^(.)\$ http://example.com/\$1 [L,R=301]*

Modify the RewriteBase if you are using Drupal in a subdirectory or in a VirtualDocumentRoot and the rewrite rules are not working properly. For example if your site is at http://example.com/drupal uncomment and modify the following line:

RewriteBase /drupal

#

If your site is running in a VirtualDocumentRoot at http://example.com/, uncomment the following line:

RewriteBase /

```
# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>

# $Id: .htaccess,v 1.90.2.5 2010/02/02 07:25:22 dries Exp $
# AddOutputFilterByType DEFLATE text/css application/x-javascript

# Sebcode: A line to cache ipad stuff for the infiniti ipad webapp
AddType text/cache-manifest .manifest
```