

```
# Use the front controller as index file. It serves as a fallback solution when
# every other rewrite/redirect fails (e.g. in an aliased environment without
# mod_rewrite). Additionally, this reduces the matching process for the
# start page (path "/") because otherwise Apache will apply the rewriting rules
# to each configured DirectoryIndex file (e.g. index.php, index.html, index.pl).
DirectoryIndex app_dev.php
```

```
# By default, Apache does not evaluate symbolic links if you did not enable this
# feature in your server configuration. Uncomment the following line if you
# install assets as symlinks or if you experience problems related to symlinks
# when compiling LESS/Sass/CoffeScript assets.
# Options FollowSymlinks
```

```
# Disabling MultiViews prevents unwanted negotiation, e.g. "/app" should not resolve
# to the front controller "/app.php" but be rewritten to "/app.php/app".
```

```
<IfModule mod_negotiation.c>
```

```
    Options -MultiViews
```

```
</IfModule>
```

```
<IfModule mod_rewrite.c>
```

```
    RewriteEngine On
```

```
    RewriteCond $1 ^$
```

```
    RewriteRule ^(.*)$ /bundles/sebkprojektor/app/app.html [L]
```

```
    RewriteCond %{DOCUMENT_ROOT}/bundles/sebkprojektor/app/$1 -f
```

```
    RewriteRule ^(.*)$ /bundles/sebkprojektor/app/$1 [L]
```

```
# Determine the RewriteBase automatically and set it as environment variable.
# If you are using Apache aliases to do mass virtual hosting or installed the
# project in a subdirectory, the base path will be prepended to allow proper
# resolution of the app.php file and to redirect to the correct URI. It will
# work in environments without path prefix as well, providing a safe, one-size
# fits all solution. But as you do not need it in this case, you can comment
# the following 2 lines to eliminate the overhead.
```

```
RewriteCond %{REQUEST_URI}::$1 ^(/.+)/(.*):;\2$
```

```
RewriteRule ^(.*) - [E=BASE:%1]
```

```
# Sets the HTTP_AUTHORIZATION header removed by apache
```

```
RewriteCond %{HTTP:Authorization} .
```

```
RewriteRule .* - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization}]
```

```

# Redirect to URI without front controller to prevent duplicate content
# (with and without `/app.php`). Only do this redirect on the initial
# rewrite by Apache and not on subsequent cycles. Otherwise we would get an
# endless redirect loop (request -> rewrite to front controller ->
# redirect -> request -> ...).
# So in case you get a "too many redirects" error or you always get redirected
# to the start page because your Apache does not expose the REDIRECT_STATUS
# environment variable, you have 2 choices:
# - disable this feature by commenting the following 2 lines or
# - use Apache >= 2.3.9 and replace all L flags by END flags and remove the
#   following RewriteCond (best solution)
RewriteCond %{ENV:REDIRECT_STATUS} ^$
RewriteRule ^app_dev\.php(/(.*)|)$ %{ENV:BASE}/$2 [R=301,L]

# If the requested filename exists, simply serve it.
# We only want to let Apache serve files and not directories.
RewriteCond %{REQUEST_FILENAME} -f
RewriteRule .? - [L]

# Rewrite all other queries to the front controller.
RewriteRule .? %{ENV:BASE}/app_dev.php [L]
</IfModule>

<IfModule !mod_rewrite.c>
  <IfModule mod_alias.c>
    # When mod_rewrite is not available, we instruct a temporary redirect of
    # the start page to the front controller explicitly so that the website
    # and the generated links can still be used.
    RedirectMatch 302 ^/$ /app_dev.php/
    # RedirectTemp cannot be used instead
  </IfModule>
</IfModule>

```