

```
# -----  
# Use UTF-8 encoding for anything served text/plain or text/html  
# -----  
AddDefaultCharset utf-8  
  
# -----  
# Force UTF-8 for a number of file formats  
# -----  
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml .txt  
  
# -----  
# JavaScript  
# -----  
AddType application/javascript js jsonp  
AddType application/json json  
  
# -----  
# Audio  
# -----  
AddType audio/ogg oga ogg  
AddType audio/mp4 m4a f4a f4b  
  
# -----  
# Video  
# -----  
AddType video/ogg ogv  
AddType video/mp4 mp4 m4v f4v f4p  
AddType video/webm webm  
AddType video/x-flv flv  
  
# -----  
# SVG  
# -----  
AddType image/svg+xml svg svgz  
AddEncoding gzip svgz  
  
# -----  
# Webfonts  
# -----  
AddType application/vnd.ms-fontobject eot  
AddType application/x-font-ttf ttf ttflink
```

```

AddType application/x-font-ttf ttf ttc
AddType font/opentype otf
AddType application/x-font-woff woff

# -----
# Assorted types
# -----
AddType image/x-icon ico
AddType image/webp webp
AddType text/cache-manifest appcache manifest
AddType text/x-component htc
AddType application/xml rss atom xml rdf
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpinstall xpi
AddType application/octet-stream safariextz
AddType application/x-web-app-manifest+json webapp
AddType text/x-vcard vcf
AddType application/x-shockwave-flash swf
AddType text/vtt vtt

# -----
# Gzip compression
# -----
<IfModule mod_deflate.c>

    # Force deflate for mangled headers
    developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-beyond-gzipping/
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXng| X-cept-Encoding| X(15)| ^(15)| -(15))$
            ^((gzip|deflate)\s*,?\s*)+ [X"-]({4,13})$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Compress all output labeled with one of the following MIME-types
    # (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
    # and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines as
    # `AddOutputFilterByType` is still in the core directives)
    <IfModule mod_filter.c>

```

```
AddOutputFilterByType DEFLATE application/atom+xml \
    application/javascript \
    application/json \
    application/rss+xml \
    application/vnd.ms-fontobject \
    application/x-font-ttf \
    application/xhtml+xml \
    application/xml \
    font/opentype \
    image/svg+xml \
    image/x-icon \
    text/css \
    text/html \
    text/plain \
    text/x-component \
    text/xml \
    text/javascript \
    application/vnd.ms-fontobject \
    application/x-font-ttf \
    font/opentype \
    application/x-font-woff
```

```
</IfModule>
```

```
</IfModule>
```

```
# -----  
# Cache  
# -----
```

```
<IfModule mod_expires.c>
```

```
<FilesMatch "\.
```

```
(ico|pdf|flv|jpg|jpeg|svg|png|gif|swf|js|xml|txt|css|woff|ttf|tcl|eot|otf)$">
```

```
Header set Cache-Control "max-age=604800, public"
```

```
</FilesMatch>
```

```
</IfModule>
```