

```
Options -Indexes +SymLinksIfOwnerMatch
```

```
DirectoryIndex index.html
```

```
<IfModule headers_module>
```

```
Header set Content-Security-Policy "default-src 'self';img-src *; style-src 'self'
https://fonts.googleapis.com; font-src https://fonts.gstatic.com;"
```

```
Header set X-Frame-Options "SAMEORIGIN"
```

```
Header set X-Content-Type-Options nosniff
```

```
Header set X-XSS-Protection "1; mode=block"
```

```
Header set Cache-Control "public, must-revalidate, proxy-revalidate, no-transform"
```

```
Header set X-UA-Compatible "IE=edge,chrome=1"
```

```
Header set Connection "Keep-Alive"
```

```
# `mod_headers` can't match based on the content-type, however, we only
```

```
# want to send this header for HTML pages and not for the other resources
```

```
<FilesMatch "\.(appcache|crx|css|eot|gif|htc|ico|jpe?
```

```
gl|js|m4a|m4v|manifest|mp4|oex|ogal|ogg|ogv|otf|pdf|png|safarixextz|svg|svgz|tfl|vcf|webapp|wet
l+xml|xpi)$">
```

```
Header set Cache-Control "public, must-revalidate, proxy-revalidate, no-transform"
```

```
Header unset X-Frame-Options
```

```
Header unset X-XSS-Protection
```

```
Header unset X-UA-Compatible
```

```
</FilesMatch>
```

```
<Files manifest.appcache>
```

```
# Header set Cache-Control "public, no-cache, no-store, must-revalidate, proxy-revalida
transform"
```

```
Header unset Accept-Ranges
```

```
</Files>
```

```
<IfModule ssl_module>
```

```
Header set Strict-Transport-Security max-age=16070400;
```

```
</IfModule>
```

```
<IfModule setenvif_module>
```

```
<FilesMatch "\.(gif|ico|jpe?gl|png|svgz?l|webp)$">
```

```
SetEnvIf Origin ":" IS_CORS
```

```
Header set Access-Control-Allow-Origin "*" env=IS_CORS
```

```
</FilesMatch>
```

```
</IfModule>
```

```
</IfModule>
```

```
# -----
```

```
# I UTF-8 encoding
```

```
|
```

```
"
```

```
# -----  
  
# Use UTF-8 encoding for anything served as `text/html` or `text/plain`.  
AddDefaultCharset utf-8  
  
# -----  
# / Proper MIME types for all files /  
# -----  
<IfModule mime_module>  
  AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml  
  # Audio  
  AddType audio/mp4 .m4a .f4a .f4b  
  AddType audio/ogg .oga .ogg  
  
  # JavaScript  
  # Normalize to standard type (it's sniffed in IE anyways):  
  # http://tools.ietf.org/html/rfc4329#section-7.2  
  AddType application/javascript .js .es6 .jsonp  
  AddType application/json .json  
  
  # Video  
  AddType video/mp4 .mp4 .m4v .f4v .f4p  
  AddType video/ogg .ogv  
  AddType video/webm .webm  
  AddType video/x-flv .flv  
  
  # Web fonts  
  AddType application/font-woff .woff  
  AddType application/font-woff2 .woff2  
  AddType application/vnd.ms-fontobject .eot  
  
  # Browsers usually ignore the font MIME types and sniff the content,  
  # however, Chrome shows a warning if other MIME types are used for the  
  # following fonts.  
  AddType application/x-font-ttf .ttc .ttf  
  AddType font/opentype .otf  
  
  # Make SVGZ fonts work on iPad:  
  # https://twitter.com/FontSquirrel/status/14855840545  
  AddType image/svg+xml .svg .svgz  
  AddEncoding gzip .svgz
```

```

# Other
AddType application/octet-stream          .safariextz
AddType application/x-chrome-extension    .crx
AddType application/x-opera-extension     .oex
AddType application/x-shockwave-flash    .swf
AddType application/x-web-app-manifest+json .webapp
AddType application/x-xpinstall          .xpi
AddType application/xml                  .atom .rdf .rss .xml
AddType text/x-markdown                  .md
AddType image/webp                       .webp
AddType image/x-icon                     .ico
AddType text/cache-manifest              .appcache .manifest
AddType text/vtt                         .vtt
AddType text/x-component                 .htc
AddType text/x-vcard                     .vcf
AddType application/pgp-keys             .pgp .PGP
</IfModule>

# Block access to backup and source files.
# These files may be left by some text editors and can pose a great security
# danger when anyone has access to them.

<FilesMatch "(^#.#|.#\.(bak|ht.#|davl|conf(ig)?|dist|fla|incl|ini|log|psd|sql|sw[op]|ascl|b:
sh|mdl|ym|l|lock|log|git.#|gpg|pgp))$" >
    Require all denied
</FilesMatch>
<FilesMatch "^(ajax|custom|unit)\.php$" >
    Require all denied
</FilesMatch>
<FilesMatch "\.html$" >
    Require all granted
</FilesMatch>
<IfModule deflate_module>
    # Force compression for mangled headers.
    # http://developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-beyond-gzipping
    <IfModule setenvif_module>
        <IfModule headers_module>
            SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\
[X^-]{4,13})$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding

```

```

    </IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule filter_module>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).
<IfModule filter_module>
    AddOutputFilterByType DEFLATE application/atom+xml \
    application/javascript \
    application/json \
    application/rss+xml \
    application/vnd.ms-fontobject \
    application/x-font-ttf \
    application/x-web-app-manifest+json \
    application/xhtml+xml \
    application/xml \
    font/opentype \
    image/svg+xml \
    image/x-icon \
    text/css \
    text/html \
    text/plain \
    text/x-component \
    text/xml
</IfModule>
</IfModule>

# -----
# | Content transformations |
# -----

# Prevent some of the mobile network providers from modifying the content of
# your site: http://www.w3.org/Protocols/rfc2616/rfc2616-sec14.html#sec14.9.5.

# -----
# | ETag removal |
# -----

# Since we're sending far-future expires headers (see below), ETags can
# be removed: http://developer.yahoo.com/performance/rules.html#etags.

```

```

# `FileETag None` is not enough for every server.
# <IfModule headers_module>
#   Header unset ETag
# </IfModule>
#
# FileETag None

# -----
# | Expires headers (for better cache control) |
# -----

# The following expires headers are set pretty far in the future. If you don't
# control versioning with filename-based cache busting, consider lowering the
# cache time for resources like CSS and JS to something like 1 week.

# The following expires headers are set pretty far in the future. If you don't
# control versioning with filename-based cache busting, consider lowering the
# cache time for resources like CSS and JS to something like 1 week.

<IfModule expires_module>
ExpiresActive on
ExpiresDefault "access plus 1 month"

# CSS
ExpiresByType text/css "access plus 1 year"

# Data interchange
ExpiresByType application/json "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType text/xml "access plus 0 seconds"

# Favicon (cannot be renamed!)
ExpiresByType image/x-icon "access plus 1 week"

# HTML components (HTCs)
ExpiresByType text/x-component "access plus 1 month"

# HTML
ExpiresByType text/html "access plus 0 seconds"

# JavaScript

```

```

ExpiresByType application/javascript      "access plus 1 year"

# Manifest files
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest          "access plus 0 seconds"

# Media
ExpiresByType audio/ogg                   "access plus 1 month"
ExpiresByType image/gif                   "access plus 1 month"
ExpiresByType image/jpeg                  "access plus 1 month"
ExpiresByType image/png                   "access plus 1 month"
ExpiresByType video/mp4                   "access plus 1 month"
ExpiresByType video/ogg                   "access plus 1 month"
ExpiresByType video/webm                  "access plus 1 month"

# Web feeds
ExpiresByType application/atom+xml         "access plus 1 hour"
ExpiresByType application/rss+xml         "access plus 1 hour"

# Web fonts
ExpiresByType application/font-woff        "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf       "access plus 1 month"
ExpiresByType font/opentype               "access plus 1 month"
ExpiresByType image/svg+xml               "access plus 1 month"
</IfModule>

# -----
# | Filename-based cache busting |
# -----

# If you're not using a build process to manage your filename version revving,
# you might want to consider enabling the following directives to route all
# requests such as /css/style.12345.css to /css/style.css.

# To understand why this is important and a better idea than *.css?v231, read:
# http://stevesouder.com/blog/2008/08/23/revving-filenames-dont-use-querystring

# -----
# | File concatenation |
# -----

```

```
# Allow concatenation from within specific CSS and JS files, e.g.:
# Inside of `script.combined.js` you could have
# <!--#include file="libs/jquery.js" -->
# <!--#include file="plugins/jquery.idletimer.js" -->
# and they would be included into this single file.

# <IfModule include_module>
#   <FilesMatch "\.(?!(combined|polyfills)\.js$)">
#     Options +Includes
#     AddOutputFilterByType INCLUDES application/javascript application/json
#     SetOutputFilter INCLUDES
#   </FilesMatch>
# </IfModule>

# -----
# | Error pages |
# -----
ErrorDocument 400 /index.html
ErrorDocument 401 /index.html
ErrorDocument 402 /index.html
ErrorDocument 403 /index.html
ErrorDocument 404 /index.html
ErrorDocument 500 /index.html
```