

```

<IfModule mod_rewrite.c>
    #Rewrite Engine Settings : Warning, AllowOverride need to be all for current folder
    RewriteEngine On
    RewriteBase /

    #If the URL start with public stop redirect
    RewriteRule ^cache - [L]
    RewriteRule ^index.php - [L]

    #If file already exists
    RewriteCond %{DOCUMENT_ROOT}/cache%(REQUEST_URI) -f
    RewriteRule ^(.*)$ cache/$1 [L]

    #Else go to controller
    RewriteRule ^(\.(*)\|)([0-9]+x[0-9]+[a-z]+[0-9]+original)\|(\.(*)$) index.php?
path=$4&format=$3&scheme=$2 [L,QSA]
</IfModule>

```

```

##### MOD_DEFLATE COMPRESSION #####

```

```

#Do not put in cache if files are already in
SetEnvIfNoCase Request_URI \.(?:gif|jpe?g|png)$ no-gzip

```

```

##### EXPIRE HEADERS #####

```

```

<IfModule mod_expires.c>
    ExpiresActive On
    ExpiresDefault "access plus 7200 seconds"
    ExpiresByType image/jpg "access plus 2592000 seconds"
    ExpiresByType image/jpeg "access plus 2592000 seconds"
    ExpiresByType image/png "access plus 2592000 seconds"
    ExpiresByType image/gif "access plus 2592000 seconds"

    AddType image/x-icon .ico
    ExpiresByType image/ico "access plus 2592000 seconds"
    ExpiresByType image/icon "access plus 2592000 seconds"
    ExpiresByType image/x-icon "access plus 2592000 seconds"
    ExpiresByType text/css "access plus 2592000 seconds"
</IfModule>

```

```

##### CACHE CONTROL HEADERS #####

```

```

<IfModule mod_headers.c>
    #see module's default document to see content...

```

```
#les proxies doivent donner le bon contenu
Header append Vary User-Agent env=!dont-vary

<FilesMatch "\\.(ico|jpe?g|png|gif|swf|gz|ttf)$">
  Header set Cache-Control "max-age=2592000, public"
</FilesMatch>

# KILL THEM ETAGS
Header unset ETag
FileETag none
</IfModule>

##### PROTECT HTACCESS FILE #####
<Files .htaccess>
  Order allow,deny
  Deny from all
</Files>

##### PROTECT FOLDER LISTING #####
Options -Indexes
```