

```
# BEGIN WP Rocket v2.6.7
# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset UTF-8
# Force UTF-8 for a number of file formats
<IfModule mod_mime.c>
AddCharset UTF-8 .atom .css .js .json .rss .vtt .xml
</IfModule>

# FileETag None is not enough for every server.
<IfModule mod_headers.c>
Header unset ETag
</IfModule>

# Since we're sending far-future expires, we don't need ETags for static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

<IfModule mod_alias.c>
<FilesMatch "\.(html|html|rtf|rtx|svg|svgz|txt|xsl|xsl|xml)$">
<IfModule mod_headers.c>
Header set X-Powered-By "WP Rocket/2.6.7"
Header unset Pragma
Header append Cache-Control "public"
Header unset Last-Modified
</IfModule>
</FilesMatch>

<FilesMatch "\.
(css|htc|js|asf|asx|wax|wmv|wmx|avi|bmp|class|divx|doc|docx|eot|exel|gif|gz|gzipped|ico|jpg|jpeg|
<IfModule mod_headers.c>
Header unset Pragma
Header append Cache-Control "public"
</IfModule>
</FilesMatch>
</IfModule>

# Expires headers (for better cache control)
<IfModule mod_expires.c>
ExpiresActive on

# Perhaps better to utilize expires module? Perhaps
```

```
# Perhaps better to whitelist expires rules? Perhaps.
ExpiresDefault "access plus 1 month"

# cache, apache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
ExpiresByType text/cache-manifest "access plus 0 seconds"

# Your document html
ExpiresByType text/html "access plus 0 seconds"

# Data
ExpiresByType text/xml "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType application/json "access plus 0 seconds"

# Feed
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/atom+xml "access plus 1 hour"

# Favicon (cannot be renamed)
ExpiresByType image/x-icon "access plus 1 week"

# Media: images, video, audio
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# HTC files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# Webfonts
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType application/x-font-woff2 "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
```

```

# CSS and JavaScript
ExpiresByType text/css          "access plus 1 year"
ExpiresByType application/javascript "access plus 1 year"

</IfModule>

# Gzip compression
<IfModule mod_deflate.c>
# Active compression
SetOutputFilter DEFLATE
# Force deflate for mangled headers
<IfModule mod_setenvif.c>
<IfModule mod_headers.c>
SetEnvIfNoCase ^(\Accept-EncodXng| X-cept-Encoding| X(15)| ~(15)| -(15))$ ^((gzip| deflate)\s*, ?)\s
RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
# Don't compress images and other uncompressible content
SetEnvIfNoCase Request_URI \
\. (? : gif| jpe?g| png| rar| zip| exe| flv| mov| wml| mp3| avi| swf| mp?g)$ no-gzip dont-vary
</IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
<IfModule mod_filter.c>
AddOutputFilterByType DEFLATE application/atom+xml \
                           application/javascript \
                           application/json \
                           application/rss+xml \
                           application/vnd.ms-fontobject \
                           application/x-font-ttf \
                           application/xhtml+xml \
                           application/xml \
                           font/opentype \
                           image/svg+xml \
                           image/x-icon \
                           text/css \
                           text/html \
                           text/plain \
                           text/x-component \
                           text/xml
</IfModule>
<IfModule mod_headers.c>

```

```

Header append Vary User-Agent env=!dont-vary
</IfModule>
</IfModule>

<IfModule mod_mime.c>
AddType text/html .html_gzip
AddEncoding gzip .html_gzip
</IfModule>
<IfModule mod_setenvif.c>
SetEnvIfNoCase Request_URI \.html_gzip$ no-gzip
</IfModule>

<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /
RewriteCond %{HTTPS} on
RewriteRule .* - [E=WPR_SSL:-https]
RewriteCond %{SERVER_PORT} ^443$
RewriteRule .* - [E=WPR_SSL:-https]
RewriteCond %{HTTP:Accept-Encoding} gzip
RewriteRule .* - [E=WPR_ENC:_gzip]
RewriteCond %{REQUEST_METHOD} GET
RewriteCond %{QUERY_STRING} =""
RewriteCond %{HTTP:Cookie} !(wordpress_logged_in_|wp-postpass_|wptouch_switch_toggle|comment
RewriteCond %{REQUEST_URI} !^(/checkout/(. *)|/cart/|/my-account/(. *)|/wc-api/v(. *)|.*/feed/)
RewriteCond %{HTTP_USER_AGENT} !^(facebookexternalhit). * [NC]
RewriteCond "/homepages/9/d278609429/htdocs/prod/costa/wp-content/cache/wp-rocket/%{HTTP_HOST}
RewriteRule .* "/homepages/9/d278609429/htdocs/prod/costa/wp-content/cache/wp-rocket/%{HTTP_
</IfModule>

# END WP Rocket

# BEGIN WordPress
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /
RewriteRule ^index\.php$ - [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index.php [L]
RewriteRule ^(.*\.js) gzip.php?type=js&file=$1
RewriteRule ^(.*\.css) gzip.php?type=css&file=$1

```

</IfModule>

END WordPress