

AddDefaultCharset UTF-8

```
# set gzip transfer if possible
# http://developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-beyond-gzipping/
<IfModule mod_headers.c>
    BrowserMatchNoCase (MSIE|Firefox|Chrome|Safari|Opera) HAVE_Accept-Encoding
    SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
    ^((gzip|deflate)\s,?\s(gzip|deflate)?|X(4,13)|^(4,13)|-(4,13))$ HAVE_Accept-Encoding
</IfModule>

# I set browser caching for all common contents
# file png
<FilesMatch "\.(png)$">
    <IfModule mod_headers.c>
        Header set Content-type "image/png"
        Header set Cache-Control "max-age=29030400, private, proxy-revalidate"
    </IfModule>
</FilesMatch>
# file jpg
<FilesMatch "\.(jpg|jpeg|jpe)$">
    <IfModule mod_headers.c>
        Header set Content-type "image/jpeg"
        Header set Cache-Control "max-age=29030400, private, proxy-revalidate"
    </IfModule>
</FilesMatch>
# file gif
<FilesMatch "\.(gif)$">
    <IfModule mod_headers.c>
        Header set Content-type "image/gif"
        Header set Cache-Control "max-age=29030400, private, proxy-revalidate"
    </IfModule>
</FilesMatch>
# file css
<FilesMatch "\.(css)$">
    <IfModule mod_headers.c>
        Header set Content-type "text/css; charset=UTF-8"
        Header set Cache-Control "max-age=29030400, private, proxy-revalidate"
    </IfModule>
</FilesMatch>
# file javascript
<FilesMatch "\.(js)$">
```

```
<FilesMatch "\.(js)$">
  <IfModule mod_headers.c>
    Header set Content-type "text/javascript; charset=UTF-8"
    Header set Cache-Control "max-age=29030400, private, proxy-revalidate"
  </IfModule>
</FilesMatch>
# file ico favicon
<FilesMatch "\.(ico)$">
  <IfModule mod_headers.c>
    Header set Content-type "image/x-icon"
    Header set Cache-Control "max-age=29030400, private, proxy-revalidate"
  </IfModule>
</FilesMatch>

# Now I set rewriting for application
RewriteEngine On
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule !\.(ico|js|jpg|css)$ index.php
```