

```
# Set the default handler.
DirectoryIndex index.php index.html index.htm

redirect /portfolio http://portfolio.rkarkut.pl

# Prevent directory listing
Options -Indexes

# Make sure MultiViews is disabled if available.
<IfModule mod_negotiation.c>
    Options -MultiViews
</IfModule>

<FilesMatch "\.(dist|dtd|markdown|md|twig|yaml|yml)|(bower|composer|jsdoc|package)\.json$">
    <IfModule mod_authz_core.c>
        Require all denied
    </IfModule>
    <IfModule !mod_authz_core.c>
        Order deny,allow
        Deny from all
    </IfModule>
</FilesMatch>

<IfModule mod_rewrite.c>
    RewriteEngine on

    RewriteRule cache/ - [F]

    # Some servers require the RewriteBase to be set. If so, set to the correct folder.
    # RewriteBase /

    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteCond %{REQUEST_URI} !=/favicon.ico
    RewriteRule ^ ./index.php [L]

</IfModule>

# set the correct mime type for woff2 font type
# =====
# If you don't get your own extensions or you want to update
```

```
# If you don't set your own mimetypes or you aren't using
# HTML5 Boilerplate Server Configs https://github.com/h5bp/server-configs-apache
# then you can uncomment (delete the hash/pound/octothorpe/number symbol)
# the section below:
```

```
<IfModule mod_mime.c>
# AddType application/font-woff2    woff2
</IfModule>
```

```
# Block access to all hidden files and directories. These types of files
# usually contain user preferences and can include private information like,
# for example, the .git or .svn directories.
```

```
<IfModule mod_rewrite.c>
  RewriteEngine On
  RewriteCond %{REQUEST_URI} "!(^/)\.well-known/([^\./]+/?)+" [NC]
  RewriteCond %{SCRIPT_FILENAME} -d [OR]
  RewriteCond %{SCRIPT_FILENAME} -f
  RewriteRule "(^/)\." - [F]
</IfModule>
```