

```

<IfModule mod_headers.c>
# Because X-UA-Compatible isn't sent to non-IE (to save header bytes),
# We need to inform proxies that content changes based on UA
Header append Vary User-Agent
# Cache control is set only if mod_headers is enabled, so that's unnecessary to declare
</IfModule>

# gzip compression.
<IfModule mod_deflate.c>

# html, txt, css, js, json, xml, htc:
AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
AddOutputFilterByType DEFLATE text/javascript application/javascript application/x-
javascript
AddOutputFilterByType DEFLATE text/xml application/xml text/x-component

# webfonts and svg:
<FilesMatch "\.(ttf|otf|eot|svg)$" >
SetOutputFilter DEFLATE
</FilesMatch>
</IfModule>

<IfModule mod_rewrite.c>
RewriteEngine On
RewriteCond %{HTTP_HOST} ^www\. steven-samson\. com
RewriteRule (.*) http://steven-samson.com/$1 [R=301,L]
</IfModule>

# Proper svg serving. Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml svg svgz
AddEncoding gzip svgz

# webfonts
AddType application/vnd.ms-fontobject eot
AddType font/truetype ttf
AddType font/opentype otf
AddType font/woff woff

# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the same name
# does not exist

```

```
does not exist
# e.g. /blog/hello : webmasterworld.com/apache/3808792.htm
Options -MultiViews
# -Indexes will have Apache block users from browsing folders without a default document
Options -Indexes
# custom 404 page
ErrorDocument 404 /404.html
# use utf-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8
# force utf-8 for a number of file formats
AddCharset utf-8 .html .css .js .xml .json .rss
# We don't need to tell everyone we're apache.
ServerSignature Off
```