

```
#
# Hey! Everything in here is better suited to httpd.conf, since
# we get a performance boost if we can turn off AllowOverride and
# not have to stat the webroot for every request. On the other
# hand, this means we never have to touch apache once it's up.
# Flexibility over performance.
#
# In an ideal world, you'd stick it in here on dev and your build
# system would bundle the changes into (a file included in) httpd.conf
# for your production deployment. Yeah. Do that.
#

# ETags are a bad idea if you have multiple web servers. We'll do
# more explicit caching with Expires headers anyway.
```

```
FileETag none
```

```
# The base set of sensible PHP options. You could put these in your
# php.ini file too, but having them in your Apache config puts
# everything in one place. Magic quotes off because they are stupid.
# Register globals off for the same reason. Track errors is so that
# we can at least get at the error messages we hide using @func().
# last_modified is a bad idea if we have any dynamic content. Short
# tags make for a few saved bytes of cruft and are fine unless you're
# running another XML preprocessor over your code (wtf?).
```

```
php_value magic_quotes_gpc 0
php_value register_globals 0
php_value magic_quotes_runtime 0
php_value track_errors 1
php_value last_modified off
php_value short_open_tag on
```

```
php_flag display_errors on
```

```
# this sets all current and future error flags on, except for E_NOTICE
# which can go fuck itself. we have some separate code for checking the
# one notice we do care about.
```

```
php_value error_reporting 2147483639
```

```
# Some basic pointers to php files
```

```
DirectoryIndex index.php
```

```
ErrorDocument 404 /404.php
```

[ErrorDocument 404 /404.php](#)

[ErrorDocument 403 /403.php](#)

Get mod_rewrite fired up

RewriteEngine on

Login stuff

RewriteRule ^signup/?\$ signup.php [L]

RewriteRule ^signin/?\$ signin.php [L]

RewriteRule ^signout/?\$ signout.php [L]

RewriteRule ^checkcookie/?\$ checkcookie.php [L]

RewriteRule ^auth/?\$ auth_callback_instagram_oauth.php?%(QUERY_STRING) [L]

RewriteRule ^signin/?\$ signin_instagram_oauth.php?%(QUERY_STRING) [L]

Password retrieval stuff

RewriteRule ^forgot/?\$ forgot.php [L]

RewriteRule ^reset/([a-zA-Z0-9]+)/?\$ reset.php?reset=\$1 [L,QSA]

Account stuff

RewriteRule ^account/?\$ account.php [L]

RewriteRule ^account/password/?\$ account_password.php [L]

RewriteRule ^account/delete/?\$ account_delete.php [L]

RewriteRule ^account/instagram/backups/?\$ account_instagram_backups.php?%(QUERY_STRING) [L]

API stuff

RewriteRule ^api/?\$ api_rest.php [L]

RewriteRule ^api/methods/?\$ api_methods.php [L]

RewriteRule ^api/methods/(.*)/?\$ api_method.php?method=\$1&%(QUERY_STRING) [L]

RewriteRule ^api/rest/(.*)/?\$ api_rest.php?method=\$1&%(QUERY_STRING) [L]

Invite code stuff

RewriteRule ^invite/?\$ invite.php?%(QUERY_STRING) [L]

RewriteRule ^invite(/([a-zA-Z0-9]+))/?\$ invite.php?code=\$2&%(QUERY_STRING) [L]

Instagram stuff

```
RewriteRule ^me(/(. *))*/?/?$ me.php?path=$2&%(QUERY_STRING) [L]

RewriteRule ^p/([a-zA-Z_0-9]+)/?$ instagram_photo.php?short_code=$1&%(QUERY_STRING) [L]

RewriteRule ^user/([0-9]+)/?$ /user/$1/photos/ [R]
RewriteRule ^user/[0-9]+/photos/([0-9]+)(/with-filter-([a-zA-Z\ ]+))/?/?$
instagram_photo.php?id=$1&filter=$3&%(QUERY_STRING) [L]

RewriteRule ^user/([0-9]+)/photos(/page([0-9]+))/?/?$ instagram_photos_user.php?
instagram_id=$1&page=$3&%(QUERY_STRING) [L]
RewriteRule ^user/([0-9]+)/photos/([a-zA-Z\ ]+)(/page([0-9]+))/?/?$
instagram_photos_user.php?instagram_id=$1&filter=$2&page=$4&%(QUERY_STRING) [L]

RewriteRule ^user/([0-9]+)/likes/([a-zA-Z\ ]+)(/page([0-9]+))/?/?$
instagram_likes_user.php?instagram_id=$1&filter=$2&page=$4&%(QUERY_STRING) [L]
RewriteRule ^user/([0-9]+)/likes/([0-9]+)(/page([0-9]+))/?/?$ instagram_likes_user.php?
instagram_id=$1&photo_owner_id=$2&page=$4&%(QUERY_STRING) [L]
RewriteRule ^user/([0-9]+)/likes(/page([0-9]+))/?/?$ instagram_likes_user.php?
instagram_id=$1&page=$3&%(QUERY_STRING) [L]

RewriteRule ^push/([a-zA-Z0-9]+)/?$ instagram_push.php?secret=$1&%(QUERY_STRING) [L]
```