```
# Set some reasonable defaults for PHP. Most of these cannot be set
# inside the script itself. For hosts that don't have .htaccess
# support but do support per-dir php.ini files, these settings are
# mirrored in php.ini
<IfModule mod_php5.c>
 php_flag short_open_tag
                                    On.
 php_flag magic_quotes_gpc
                                   Off
 php_flag magic_quotes_sybase
                                    Off
 php_flag magic_quotes_runtime
                                    Off
 php_flag register_globals
                                   Off
 php_flag session.auto_start
                                    Off
 php_flag suhosin, session, encrypt
                                    Off
 php_value upload_max_filesize
                                    20M
 php_value post_max_size
                               100M
# Try to disable the parts of mod_security that interfere with the Flash uploader
<IfModule mod_security.c>
 SecFilterEngine Off
 SecFilterScanPOST Off
</If Module>
# Increase security by uncommenting this block. It keeps browsers
# from seeing support files that they shouldn't have access to. We
# comment this out because Apache2 requires some minor configuration
# in order for you to use it. You must specify "AllowOverride Limit"
# in your Apache2 config file before you uncomment this block or
# you'll get an "Internal Server Error".
# <FilesMatch "(\.(class|fla|gitignore|inc|ini|sql|txt)|(README|LICENSE|.build_number))$">
   Order deny, allow
   Deny from all
# </FilesMatch>
# <FilesMatch "robots txt">
  Order allow, deny
   Allow from all
# </FilesMatch>
```

```
# Improve performance by uncommenting this block. It tells the
# browser that your images don't change very often so it won't keep
# asking for them.  If you get an error after uncommenting this, make
# sure you specify "AuthConfig Indexes" in your Apache config file.
# <IfModule mod_expires.c>
   ExpiresActive On
   # Cache all files for a month after access (A).
   ExpiresDefault A2678400
   # Do not cache dynamically generated pages.
   ExpiresByType text/html A1
#
# </IfModule>
# You can use the mod_rewrite Apache module to get rid of the
# "index.php" from your Gallery 3 urls. Uncomment the block below
# inside the <IfModule> ... </IfModule> lines and then edit the
# RewriteBase line to match your Gallery 3 URL.
# Here are some RewriteBase values:
                                       RewriteBase line
   Galleru 3 URL
   _____
                                        ______
#
   http://example.com/gallery3
                                       RewriteBase /gallery3
#
   http://example.com/~bob/photos
                                      - RewriteBase /~bob/photos
#
   http://gallery3.example.com/
                                       -RewriteBase /
#
#
# Then just use your Gallery 3 without the index.php in the url.
# NOTE: future upgrades of Gallery 3 will overwrite this file! If you
# want these changes to be persistent, talk to your system admin about
# putting this block into your Apache config files.
#
<IfModule mod_rewrite.c>
  Options +FollowSymLinks
  RewriteEnaine On
  RewriteBase /gallery3/
  RewriteCond %(REQUEST_FILENAME) !-f
  RewriteCond %(REQUEST_FILENAME) ! -d
  RewriteRule ^(.*)$ index.php?kohana_uri=$1 [QSA,PT,L]
  RewriteRule ^$ index.php?kohana_uri=$1 [QSA,PT,L]
  RewriteRule ^index.php/(.*) $1 [QSA,R,L]
 </IfModule>
```