

```
# BEGIN h5bp
# https://github.com/h5bp/server-configs
<IfModule mod_mime.c>

# Audio
AddType audio/mp4 m4a f4a f4b
AddType audio/ogg oga ogg opus

# Data interchange
AddType application/json json map
AddType application/ld+json jsonld

# JavaScript
# Normalize to standard type.
# http://tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript js

# Manifest files

# <Files "manifest.json">
# AddType application/manifest+json json
# </Files>

AddType application/x-web-app-manifest+json webapp
AddType text/cache-manifest appcache manifest

# Video
AddType video/mp4 f4v f4p m4v mp4
AddType video/ogg ogv
AddType video/webm webm
AddType video/x-flv flv

# Web fonts
AddType application/font-woff woff
AddType application/vnd.ms-fontobject eot

# Browsers usually ignore the font media types and simply sniff
# the bytes to figure out the font type.
# http://mimesniff.spec.whatwg.org/#matching-a-font-type-pattern

# Change browser cache-control headers if any other media types are used
```

```
# Unrome however, shows a warning if any other media types are used  
# for the following fonts.
```

```
AddType application/x-font-ttf ttc ttf  
AddType font/opentype otf
```

```
# Make SVGZ fonts work on the iPad.  
# https://twitter.com/FontSquirrel/status/14855840545
```

```
AddType image/svg+xml svg svgz  
AddEncoding gzip svgz
```

```
# Other
```

```
AddType application/octet-stream safariextz  
AddType application/x-chrome-extension crx  
AddType application/x-opera-extension oex  
AddType application/x-xpinstall xpi  
AddType application/xml atom rdf rss xml  
AddType image/webp webp  
AddType image/x-icon cur ico  
AddType text/vtt vtt  
AddType text/x-component htc  
AddType text/x-vcard vcf
```

```
</IfModule>
```

```
<IfModule mod_deflate.c>
```

```
# Force compression for mangled headers.  
# http://developer.yahoo.com/blogs/ymdn/posts/2010/12/pushing-beyond-gzipping
```

```
<IfModule mod_setenvif.c>
```

```
  <IfModule mod_headers.c>
```

```
    SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
```

```
    ^((gzip|deflate)\s*,?\s*)+([X"-]{4,13})$ HAVE_Accept-Encoding
```

```
    RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
```

```
  </IfModule>
```

```
</IfModule>
```

```
# Compress all output labeled with one of the following media types  
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`  
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines  
# as `AddOutputFilterByType` is still in the core directives).
```

```
## vim: set fdm=marker:
```

```
#</IfModule mod_filter.c>
```

```
AddOutputFilterByType DEFLATE application/atom+xml \  
    application/javascript \  
    application/json \  
    application/ld+json \  
    application/manifest+json \  
    application/rss+xml \  
    application/vnd.ms-fontobject \  
    application/x-font-ttf \  
    application/x-web-app-manifest+json \  
    application/xhtml+xml \  
    application/xml \  
    font/opentype \  
    image/svg+xml \  
    image/x-icon \  
    text/css \  
    text/html \  
    text/plain \  
    text/vtt \  
    text/x-component \  
    text/xml
```

```
#</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
Header unset ETag
```

```
</IfModule>
```

```
FileETag None
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
```

```
ExpiresDefault "access plus 1 month"
```

```
# CSS
```

```
ExpiresByType text/css "access plus 1 year"
```

```
# Data interchange
```

```
ExpiresByType application/json "access plus 0 seconds"
```

```
ExpiresByType application/ld+json "access plus 0 seconds"  
ExpiresByType application/xml "access plus 0 seconds"  
ExpiresByType text/xml "access plus 0 seconds"
```

Favicon (cannot be renamed!) and cursor images

```
ExpiresByType image/x-icon "access plus 1 week"
```

HTML components (HTCs)

```
ExpiresByType text/x-component "access plus 1 month"
```

HTML

```
ExpiresByType text/html "access plus 0 seconds"
```

JavaScript

```
ExpiresByType application/javascript "access plus 1 year"
```

Manifest files

```
ExpiresByType application/manifest+json "access plus 1 year"  
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"  
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

Media

```
ExpiresByType audio/ogg "access plus 1 month"  
ExpiresByType image/gif "access plus 1 month"  
ExpiresByType image/jpeg "access plus 1 month"  
ExpiresByType image/png "access plus 1 month"  
ExpiresByType video/mp4 "access plus 1 month"  
ExpiresByType video/ogg "access plus 1 month"  
ExpiresByType video/webm "access plus 1 month"
```

Web feeds

```
ExpiresByType application/atom+xml "access plus 1 hour"  
ExpiresByType application/rss+xml "access plus 1 hour"
```

Web fonts

```
ExpiresByType application/font-woff "access plus 1 month"  
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"  
ExpiresByType application/x-font-ttf "access plus 1 month"  
ExpiresByType font/opentype "access plus 1 month"  
ExpiresByType image/svg+xml "access plus 1 month"
```

```
</IfModule>
```

```
# END h5bp
```

```
# BEGIN WordPress
```

```
<IfModule mod_rewrite.c>
```

```
    RewriteEngine On
```

```
    RewriteBase /
```

```
    RewriteRule ^index\.php$ - [L]
```

```
    RewriteCond %{REQUEST_FILENAME} !-f
```

```
    RewriteCond %{REQUEST_FILENAME} !-d
```

```
    RewriteRule . /index.php [L]
```

```
</IfModule>
```

```
# END WordPress
```