

Options +FollowSymLinks -Indexes

<IfModule mod_env.c>

No GZIP for script-based file downloads.

SetEnv no-gzip 1

</IfModule>

<IfModule mod_rewrite.c>

Enable rewrite and configure base.

RewriteEngine On

RewriteBase /bcd/

Initialize all environment variables we're using below.

RewriteCond %{ENV:s2member_file_download_setup} !^complete\$

RewriteRule ^(.*)\$ -

[E=s2member_file_download_wp_vdir: 0,E=s2member_file_download: \$1,E=s2member_file_stream: 0,E=:

Handle virtual directories, common on multisite networks.

RewriteCond %{ENV:s2member_file_download_wp_vdir_check} !^complete\$

RewriteCond %{THE_REQUEST} ^(?: GET| HEAD)(?: [\]+)(?: /bcd/)([_0-9a-zA-Z\]+)(?: wp-content/

RewriteRule ^(.*)\$ - [E=s2member_file_download_wp_vdir: ,E=s2member_file_download_wp_vdir: :

Handle streaming download requests via the rewrite engine.

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-stream/)(.+) \$

RewriteRule ^(.*)\$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%2,E=s2member

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-stream-(.+)/)(.+) \$

RewriteRule ^(.*)\$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member

Handle inline file requests via the rewrite engine.

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-inline/)(.+) \$

RewriteRule ^(.*)\$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%2,E=s2member

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-inline-(.+)/)(.+) \$

RewriteRule ^(.*)\$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member

Handle storage specifications via the rewrite engine.

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-storage-(.+)/)(.+) \$

RewriteRule ^(.*)\$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member

Handle requests without the rewrite engine via the rewrite engine.

```

# handle remote authorization requests via the rewrite engine.
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-remote/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%2,E=s2member

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-remote-(.+)/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member

# Handle SSL file requests via the rewrite engine.
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-ssl/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%2,E=s2member

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-ssl-(.+)/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member

# Handle file download keys via the rewrite engine.
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-download-key-(.+)/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member

# Handle confirmations having been skipped via the rewrite engine.
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-skip-confirmation/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%2,E=s2member

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-skip-confirmation-(.+)/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member

# Cleanup variables not used in this request. Looking for `0` values.
RewriteCond %{ENV:s2member_file_download_wp_vdir} ^0$
RewriteRule ^(.*)$ - [E=s2member_file_download_wp_vdir:]

RewriteCond %{ENV:s2member_file_stream} ^0$
RewriteRule ^(.*)$ - [E=s2member_file_stream:]

RewriteCond %{ENV:s2member_file_inline} ^0$
RewriteRule ^(.*)$ - [E=s2member_file_inline:]

RewriteCond %{ENV:s2member_file_storage} ^0$
RewriteRule ^(.*)$ - [E=s2member_file_storage:]

RewriteCond %{ENV:s2member_file_remote} ^0$
RewriteRule ^(.*)$ - [E=s2member_file_remote:]

```

```
RewriteCond %(ENV: s2member_file_ssl) ^0$
```

```
RewriteRule ^(.*)$ - [E=s2member_file_ssl: ]
```

```
RewriteCond %(ENV: s2member_file_download_key) ^0$
```

```
RewriteRule ^(.*)$ - [E=s2member_file_download_key: ]
```

```
RewriteCond %(ENV: s2member_skip_confirmation) ^0$
```

```
RewriteRule ^(.*)$ - [E=s2member_skip_confirmation: ]
```

```
# Put everything together now and process the internal rewrite.
```

```
RewriteRule ^(.*)$ %(ENV: s2member_file_download_wp_vdir)?s2member_file_download=%(ENV: s2m  
(ENV: s2member_skip_confirmation) [QSA, L]
```

```
</IfModule>
```

```
<IfModule !mod_rewrite.c>
```

```
deny from all
```

```
</IfModule>
```