```
# Use the front controller as index file. It serves as fallback solution when
# every other rewrite/redirect fails (e.g. in an aliased environment without
# mod_rewrite). Additionally, this reduces the matching process for the
# startpage (path "/") because otherwise Apache will apply the rewritting rules
# to each configured DirectoryIndex file (e.g. index.php, index.html, index.pl).
DirectoryIndex app.php
<IfModule mod_rewrite.c>
    RewriteEngine On
    # Determine the RewriteBase automatically and set it as environment variable.
    # If you are using Apache aliases to do mass virtual hosting or installed the
    # project in a subdirectory, the base path will be prepended to allow proper
    # resolution of the app php file and to redirect to the correct URI. It will
    # work in environments without path prefix as well, providing a safe, one-size
    # fits all solution. But as you do not need it in this case, you can comment
    # the following 2 lines to eliminate the overhead.
    RewriteCond %(REQUEST_URI)::$1 ^(/.+)/(.*)::\2$
    RewriteRule ^(.*) - [E=BASE: %1]
    # Redirect to URI without front controller to prevent duplicate content
    # (with and without `/app.php`). Only do this redirect on the initial
    # rewrite by Apache and not on subsequent cycles. Otherwise we would get an
    # endless redirect loop (request -> rewrite to front controller ->
    # redirect -> request -> ...).
    # So in case you get a "too many redirects" error or you always get redirected
    # to the startpage because your Apache does not expose the REDIRECT_STATUS
    # environment variable, you have 2 choices:
    # - disable this feature by commenting the following 2 lines or
    # - use Apache >= 2.3.9 and replace all L flags by END flags and remove the
    # following RewriteCond (best solution)
    RewriteCond %(ENV: REDIRECT_STATUS) ^$
    RewriteRule ^app\.php(/(.*)|$) %(ENV:BASE)/$2 [R=301,L]
    # If the requested filename exists, simply serve it.
    # We only want to let Apache serve files and not directories.
    RewriteCond %(REQUEST_FILENAME) -f
    RewriteRule .? - [L]
```

# Day and the color of the factor and the factor and the factor of the f