

AddDefaultCharset UTF-8

```
#=====
```

```
#mod_deflate-Modul Deflate Kompression für Textbasierte Dateien aktivieren
```

```
<IfModule mod_deflate.c>
```

```
  AddOutputFilterByType DEFLATE text/html text/plain text/xml text/css text/javascript  
  application/javascript
```

```
</IfModule>
```

```
#=====
```

```
#mod_expires-Modul Expires Header unterschiedlicher Dateien für Browser Caching  
aktivieren
```

```
<IfModule mod_expires.c>
```

```
  ExpiresActive on
```

```
  ExpiresDefault                                     "access plus 1 month"
```

```
# Your document html
```

```
  ExpiresByType text/html                           "access plus 0 seconds"
```

```
# Data
```

```
  ExpiresByType text/xml                             "access plus 0 seconds"
```

```
  ExpiresByType application/xml                      "access plus 0 seconds"
```

```
  ExpiresByType application/json                    "access plus 0 seconds"
```

```
# RSS feed
```

```
  ExpiresByType application/rss+xml                 "access plus 1 hour"
```

```
# Favicon (cannot be renamed)
```

```
  ExpiresByType image/x-icon                         "access plus 1 week"
```

```
# Media: images, video, audio
```

```
  ExpiresByType image/gif                            "access plus 1 month"
```

```
  ExpiresByType image/png                            "access plus 1 month"
```

```
  ExpiresByType image/jpg                            "access plus 1 month"
```

```
  ExpiresByType image/jpeg                           "access plus 1 month"
```

```
  ExpiresByType video/ogg                             "access plus 1 month"
```

```
  ExpiresByType audio/ogg                             "access plus 1 month"
```

```
  ExpiresByType application/javascript                "access plus 1 month"
```

```

ExpiresByType video/mp4                access plus 1 month
ExpiresByType video/webm               "access plus 1 month"

# Webfonts
ExpiresByType font/truetype             "access plus 1 month"
ExpiresByType font/opentype             "access plus 1 month"
ExpiresByType application/x-font-woff  "access plus 1 month"
ExpiresByType image/svg+xml             "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# CSS and JavaScript
ExpiresByType text/css                   "access plus 1 year"
ExpiresByType application/javascript     "access plus 1 year"
ExpiresByType text/javascript            "access plus 1 year"

<IfModule mod_headers.c>
    Header append Vary User-Agent
    Header append Cache-Control "public"
</IfModule>

</IfModule>

#=====

# Apache Befehle um das Tool SmartOptimizer einsetzen zu können
<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteBase /baress/optimiert/
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteRule ^(\.*/)(js|css)$ smartoptimizer/?$1
    <IfModule mod_expires.c>
        RewriteCond %{REQUEST_FILENAME} -f
        RewriteRule ^(\.*/)(js|css|html?|xml|txt)$ smartoptimizer/?$1
    </IfModule>
    <IfModule !mod_expires.c>
        RewriteCond %{REQUEST_FILENAME} -f
        RewriteRule ^(\.*/)(gif|jpg|jpeg|png|swf|css|js|html?|xml|txt)$ smartoptimizer/?$1
    </IfModule>
</IfModule>
<FilesMatch "\.(gif|jpg|jpeg|png|swf|css|js|html?|xml|txt)$">
    --

```

```
FileETag none
</FilesMatch>
```