

```

<IfModule mod_rewrite.c>
    RewriteEngine On

    # JS and CSS files always go through the Burn library and stop there.
    RewriteRule ^(\.+)/([\^\.]+)\.(js|css)$ lib/Burn/proxy.php?path=$1&file=$2&ext=$3 [L]
    RewriteRule ^lib/Burn/proxy.php?(.*)$ - [NC,L]

    # First rewrite everything into the public directory.
    RewriteCond %{REQUEST_URI} !public
    RewriteCond $1 !^$
    RewriteRule ^(.*)$ public/$1 [NC]

    # Stop rewriting for any files that exist.
    RewriteCond %{REQUEST_FILENAME} -s [OR]
    RewriteCond %{REQUEST_FILENAME} -l [OR]
    RewriteCond %{REQUEST_FILENAME} -d
    RewriteRule ^(.*)$ - [NC,L]

    # Otherwise rewrite back to original url and serve through index.php.
    RewriteRule ^public/(.*)$ $1 [NC]

    RewriteCond $1 !^scripts
    RewriteRule ^(.*)$ index.php [NC,L]
</IfModule>

<IfModule mod_deflate.c>
    AddOutputFilterByType DEFLATE text/html text/plain text/xml application/x-javascript
    text/javascript text/css
</IfModule>

<IfModule mod_expires.c>
    ExpiresActive On
    ExpiresDefault A0
    ExpiresByType image/ico A86400
    ExpiresByType image/gif A86400
    ExpiresByType image/png A86400
    ExpiresByType image/jpeg A86400
    ExpiresByType image/x-icon A86400
    ExpiresByType text/css A86400
    ExpiresByType text/javascript A86400
    ExpiresByType application/x-javascript A86400

```

```
ExpiresByType application/x-javascript 86400
ExpiresByType application/x-shockwave-flash 86400
ExpiresByType application/pdf 86400
ExpiresByType video/x-flv 86400
```

```
</IfModule>
```