

```
#protect cli.php
Order Deny,Allow
Allow from All
<Files "cli.php">
Deny from All
</Files>
```

```
#one possible way to determine the current environment (local dev system, production server, ...)
#use getenv('qf_env') in your index/bootstrap script to read this value
#SetEnv qf_env "prod"
```

```
RewriteEngine on
```

```
#i18n
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^([a-z]{2})/(.*)$ index.php?l=language=$1&route=$2 [L,QSA]
```

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^(.*)$ index.php?route=$1 [L,QSA]
```

```
AddDefaultCharset utf-8
```

```
<IfModule mod_deflate.c>
SetOutputFilter DEFLATE
</IfModule>
```

```
<IfModule mod_expires.c>
<Files ~ "\.(png|gif|jpg|jpeg|js|css|ico|eot|ttf|otf|svg)$">
ExpiresActive On
ExpiresDefault "now plus 1 years"
</Files>
</IfModule>
```

```
<Files ~ "\.php$">
FileETag None
Header set Cache-Control "no-cache, must-revalidate, max-age=0"
Header set Pragma "no-cache"
</Files>
```