

```
#Sets ServerAddress from Server_Addr from the header and only allows that ip address to
access SoapServerAuthenticationLayer.php
SetEnvIf Server_Addr ^\b(?: \d{1,3}\.){3}\d{1,3}\b ServerAddress
#SetEnvIf Server_Addr ^\b(?: (?; 25[0-5]| 2[0-4][0-9]| [01]?[0-9][0-9]?)\.(?; 25[0-5]| 2[0-
4][0-9]| [01]?[0-9][0-9]?)\b ServerAddress
#SetEnvIf Server_Addr ^\b(25[0-5]| 2[0-4][0-9]| [01]?[0-9][0-9]?)\.(25[0-5]| 2[0-4][0-9]|
[01]?[0-9][0-9]?)\.(25[0-5]| 2[0-4][0-9]| [01]?[0-9][0-9]?)\.(25[0-5]| 2[0-4][0-9]| [01]?[0-9]
[0-9]?)\b ServerAddress
#SetEnvIf Server_Addr ^\b\d{1,3}\. \d{1,3}\. \d{1,3}\. \d{1,3}\b ServerAddress
```

```
<Files SoapServerAuthenticationLayer.php>
```

```
order deny,allow
```

```
deny from all
```

```
allow from env=ServerAddress
```

```
</Files>
```