

```
#####  
## uncomment these lines for CGI mode  
## make sure to specify the correct cgi php binary file name  
## it might be /cgi-bin/php-cgi
```

```
# Action php5-cgi /cgi-bin/php5-cgi  
# AddHandler php5-cgi .php
```

```
#####  
## this line is specific for 1and1 hosting
```

```
    #AddType x-mapp-php5 .php  
    #AddHandler x-mapp-php5 .php
```

```
#####  
## default index file
```

```
    DirectoryIndex index.php
```

```
<IfModule mod_php5.c>
```

```
#####  
## adjust memory limit
```

```
    php_value memory_limit 256M  
    php_value max_execution_time 18000
```

```
#####  
## disable magic quotes for php request vars
```

```
    php_flag magic_quotes_gpc off
```

```
#####  
## disable automatic session start  
## before autoload was initialized
```

```
    php_flag session.auto_start off
```

```
#####  
## enable resulting html compression
```

```
#php_flag zlib.output_compression on

#####
# disable user agent verification to not break multiple image upload

php_flag suhosin.session.cryptua off

#####
# turn off compatibility with PHP4 when dealing with objects

php_flag zend.zel_compatibility_mode Off

</IfModule>

<IfModule mod_rewrite.c>

#####
## enable rewrites

Options +FollowSymLinks
RewriteEngine on

## always send 404 on missing files in these folders

RewriteCond %{REQUEST_URI} !^(media|skin|js)/

#####
## never rewrite for existing files, directories and links

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_FILENAME} !-l

#####
## rewrite everything else to index.php

RewriteRule .* index.php [L]

</IfModule>

.....
```

```
#####  
## Prevent character encoding issues from server overrides  
## If you still have problems, use the second line instead
```

```
AddDefaultCharset Off  
#AddDefaultCharset UTF-8
```

```
<IfModule mod_expires.c>
```

```
#####  
## Add default Expires header  
## http://developer.yahoo.com/performance/rules.html#expires
```

```
ExpiresDefault "access plus 1 year"
```

```
</IfModule>
```

```
#####  
## By default allow all access
```

```
Order allow,deny  
Allow from all
```