

```
# fail-safe in case the conf file doesn't have it
```

```
Options All -Indexes
```

```
RewriteEngine on
```

```
# CUSTOM SERVER VARS
```

```
# You must use 'HTTP_' as prefix when setting custom vars.
```

```
# This a security check on media temple servers
```

```
RewriteRule ^ - [E=HTTP_WP_VERSION_FOLDER_NAME: wordpress-4. x. x]
```

```
# fail-safe for apache redirects
```

```
SetEnvIf REDIRECT_HTTP_WP_VERSION_FOLDER_NAME (.+) HTTP_WP_VERSION_FOLDER_NAME=$1
```

```
# IMPORTANT: Do not change the order of the 3 rewrites below
```

```
RewriteCond %{SERVER_NAME} !vermilion\.com
```

```
RewriteRule ^ - [E=HTTP_APP_ENVIRONMENT: prod]
```

```
RewriteCond %{SERVER_NAME} (\.vermilion\.com)
```

```
RewriteRule ^ - [E=HTTP_APP_ENVIRONMENT: staging]
```

```
RewriteCond %{SERVER_NAME} \.dev
```

```
RewriteRule ^ - [E=HTTP_APP_ENVIRONMENT: dev]
```

```
# fail-safe for apache redirects
```

```
SetEnvIf REDIRECT_HTTP_APP_ENVIRONMENT (.+) HTTP_APP_ENVIRONMENT=$1
```

```
# WP REWRITES/REDIRECTS
```

```
RewriteRule ^xmlrpc\.php(.*) %{ENV: HTTP_WP_VERSION_FOLDER_NAME}/xmlrpc.php$1 [L, QSA]
```

```
RewriteRule ^wp\-cron\.php(.*) %{ENV: HTTP_WP_VERSION_FOLDER_NAME}/wp-cron.php$1 [L, QSA]
```

```
RewriteRule ^wp\-trackback\.php(.*) %{ENV: HTTP_WP_VERSION_FOLDER_NAME}/wp-trackback.php$1  
[L, QSA]
```

```
RewriteRule ^wp\-comments\-post\.php(.*) %{ENV: HTTP_WP_VERSION_FOLDER_NAME}/wp-comments-  
post.php$1 [L, QSA]
```

```
RewriteRule ^wp\-mail\.php(.*) %{ENV: HTTP_WP_VERSION_FOLDER_NAME}/wp-mail.php$1 [L, QSA]
```

```
RewriteRule ^wp-content(.*) /app/wp-content$1 [L]
```

```
RewriteRule ^wp-includes(.*) /%{ENV: HTTP_WP_VERSION_FOLDER_NAME}/wp-includes$1 [L, QSA]
```

```
RewriteRule ^wp-admin(.*) %{ENV: HTTP_WP_VERSION_FOLDER_NAME}/wp-admin$1 [L, QSA]
```

```
RewriteRule ^(.*) %{ENV: HTTP_WP_VERSION_FOLDER_NAME}/$1 [L, QSA]
```

```
RewriteRule wp-login\.php$ / %ENV: HTTP_WP_VERSION_FOLDER_NAME / wp-login.php$1 [L, QSA]
```

```
RewriteRule ^%{ENV: HTTP_WP_VERSION_FOLDER_NAME}/index\.php$ - [L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule . %ENV: HTTP_WP_VERSION_FOLDER_NAME /index.php [L]
```

```
RewriteRule ^(/)?$ %ENV: HTTP_WP_VERSION_FOLDER_NAME /index.php [L]
```

LAZY LOADING IMAGES

```
RewriteCond %{QUERY_STRING} lazy_bg=true
```

```
RewriteCond %{QUERY_STRING} lazy_quality=(. *)
```

```
RewriteRule (. *) (\.jpg|\.jpeg|\.png|\.gif) app/wp-content/lazy-images/get-image.php?
```

```
image_file_path=$1$2&lazy_bg=true&lazy_quality=%1 [L]
```

DENY ACCESS TO FILES/DIRECTORIES

If you are going to forbid access to a directory, do something like the below (commented out).

```
#RewriteRule ^folder_name(. *) - [F,L,NC]
```

forbid access to certain files by name

```
<FilesMatch "(\\.mdl|\\.git|\\.gitignore|\\.sql|\\.sql.gz)">
```

```
Order Allow,Deny
```

```
Deny from all
```

```
</FilesMatch>
```

OPTIMIZATION

```
<IfModule mod_headers.c>
```

```
Header unset ETag
```

```
FileETag none
```

```
</IfModule>
```

```
AddOutputFilterByType DEFLATE text/plain
```

```
AddOutputFilterByType DEFLATE text/html
```

```
AddOutputFilterByType DEFLATE text/xml
```

```
AddOutputFilterByType DEFLATE text/css
```

```
AddOutputFilterByType DEFLATE application/xml
```

```
AddOutputFilterByType DEFLATE application/xhtml+xml
```

```
AddOutputFilterByType DEFLATE application/rss+xml
```

```
AddOutputFilterByType DEFLATE application/javascript
```

```
AddOutputFilterByType DEFLATE application/x-javascript
```

```
<ifModule mod_expires.c>
```

```
ExpiresActive On
```

```
ExpiresByType image/jpg "access plus 1 month"
```

```
ExpiresByType image/jpeg "access plus 1 month"
```

```
ExpiresByType image/gif "access plus 1 month"
```

```
ExpiresByType image/png "access plus 1 month"
```

```
ExpiresByType text/css "access plus 1 month"
```

```
ExpiresByType application/pdf "access plus 1 month"
```

```
ExpiresByType text/x-javascript "access plus 1 month"
```

```
ExpiresByType application/x-shockwave-flash "access plus 1 month"
```

```
ExpiresByType image/x-icon "access plus 1 year"
```

```
ExpiresDefault "access plus 2 days"
```

```
</ifModule>
```