

```
#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|themel|tpl(\. php)?|xhtml|svn-
base)$|^(\code-style\.|Entries.|Repository|Root|Tag|Template|all-
wcprops|entries|format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Override PHP settings. More in sites/default/settings.php
# but the following cannot be changed at runtime.

# PHP 4, Apache 1.
<IfModule mod_php4.c>
    php_value magic_quotes_gpc            0
    php_value register_globals            0
    php_value session.auto_start         0
    php_value mbstring.http_input        pass
    php_value mbstring.http_output        pass
    php_value mbstring.encoding_translation 0
</IfModule>

# PHP 4, Apache 2
```

```
# PHP 4, Apache 2.
```

```
<IfModule sapi_apache2.c>  
    php_value magic_quotes_gpc           0  
    php_value register_globals           0  
    php_value session.auto_start        0  
    php_value mbstring.http_input       pass  
    php_value mbstring.http_output      pass  
    php_value mbstring.encoding_transl  0  
</IfModule>
```

```
# PHP 5, Apache 1 and 2.
```

```
<IfModule mod_php5.c>  
    php_value magic_quotes_gpc           0  
    php_value register_globals           0  
    php_value session.auto_start        0  
    php_value mbstring.http_input       pass  
    php_value mbstring.http_output      pass  
    php_value mbstring.encoding_transl  0  
    php_value memory_limit               256M  
    php_value upload_max_filesize       30M  
    php_flag display_startup_errors     on  
    php_flag display_errors             on  
</IfModule>
```

```
# Requires mod_expires to be enabled.
```

```
<IfModule mod_expires.c>
```

```
    # Enable expirations.
```

```
    ExpiresActive On
```

```
    # Cache all files for 2 weeks after access (A).
```

```
    ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

```
    # Do not allow PHP scripts to be cached unless they explicitly send cache  
# headers themselves. Otherwise all scripts would have to overwrite the  
# headers set by mod_expires if they want another caching behavior. This may  
# fail if an error occurs early in the bootstrap process, and it may cause  
# problems if a non-Drupal PHP file is installed in a subdirectory.
```

```
    ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

```

# Various rewrite rules.
<IfModule mod_rewrite.c>
    RewriteEngine on

    RewriteCond %{HTTP_HOST} www.americanimmigrationcouncil.org
    RewriteCond %{HTTP_HOST} americanimmigrationcouncil.org
    RewriteRule ^litigation/unconstitutional-conditions-cbp-detention-facilities-challenged-
class-action-lawsuit http://www.legalactioncenter.org/litigation/unconstitutional-
conditions-cbp-detention-facilities-challenged-class-action-lawsuit [R,L]
    RewriteCond %{HTTP_HOST} www.americanimmigrationcouncil.org
    RewriteCond %{HTTP_HOST} americanimmigrationcouncil.org
    RewriteRule ^just-facts/way-too-long-prolonged-detention-border-patrol-holding-cells-
government-records-show http://immigrationpolicy.org/just-facts/way-too-long-prolonged-
detention-border-patrol-holding-cells-government-records-show [R,L]

# If your site can be accessed both with and without the 'www.' prefix, you
# can use one of the following settings to redirect users to your preferred
# URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
#
# To redirect all users to access the site WITH the 'www.' prefix,
# (http://example.com/... will be redirected to http://www.example.com/...)
# adapt and uncomment the following:
# RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
# RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
#
# To redirect all users to access the site WITHOUT the 'www.' prefix,
# (http://www.example.com/... will be redirected to http://example.com/...)
# uncomment and adapt the following:
# RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
# RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]

# Modify the RewriteBase if you are using Drupal in a subdirectory or in a
# VirtualDocumentRoot and the rewrite rules are not working properly.
# For example if your site is at http://example.com/drupal uncomment and
# modify the following line:
# RewriteBase /drupal
#
# If your site is running in a VirtualDocumentRoot at http://example.com/,
# uncomment the following line:
# RewriteBase /

```

```
# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>

# $Id$
# Set the default handler.
DirectoryIndex index.php
```