

Header always set Access-Control-Allow-Origin "*"

Header always set Access-Control-Allow-Methods "POST, GET, OPTIONS"

Header always set Access-Control-Allow-Headers "X-Accept-Charset, X-Accept, Content-Type, Origin, Accept-Encoding"

```
<IfModule mod_maxmindedb.c>
```

```
MaxMindDBEnable On
```

```
MaxMindDBFile CITY_DB /opt/maxmind/GeoLite2-City.mmdb
```

```
MaxMindDBEnv MM_COUNTRY_CODE CITY_DB/country/iso_code
```

```
MaxMindDBEnv MM_COUNTRY_NAME CITY_DB/country/names/en
```

```
MaxMindDBEnv MM_CITY_NAME CITY_DB/city/names/en
```

```
MaxMindDBEnv MM_LONGITUDE CITY_DB/location/longitude
```

```
MaxMindDBEnv MM_LATITUDE CITY_DB/location/latitude
```

```
MaxMindDBEnv MM_POSTAL_CODE CITY_DB/postal/code
```

```
MaxMindDBEnv MM_REGION_CODE CITY_DB/subdivisions/0/iso_code
```

```
MaxMindDBEnv MM_REGION_NAME CITY_DB/subdivisions/0/names/en
```

```
</IfModule>
```