

```
# Enable rewrite engine and route requests to framework
RewriteEngine On

# Some servers require you to specify the `RewriteBase` directive
# In such cases, it should be the path (relative to the document root)
# containing this .htaccess file
#
# RewriteBase /

RewriteRule ^lib/ usr - [R=404]

RewriteCond %{REQUEST_FILENAME} !-l
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule .* index.php [L,QSA]
RewriteRule .* - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization},L]

# Disable ETags
<IfModule mod_header.c>
    Header Unset ETag
    FileETag none
</IfModule>

# Mime types
<IfModule mod_mime.c>
    AddType image/svg+xml .svg
    AddType image/vnd.microsoft.icon .cur
    AddType application/vnd.ms-fontobject .eot
    AddType application/font-sfnt .ttf
    AddType application/font-woff .woff
</IfModule>

# Default expires header if none specified (stay in browser cache for 10 days)
<IfModule mod_expires.c>
    ExpiresActive On
    ExpiresByType text/css A864000
    ExpiresByType application/javascript A864000
    ExpiresByType image/gif A864000
    ExpiresByType image/png A864000
    ExpiresByType image/jpeg A864000
    ExpiresByType image/svg+xml A864000
```

```
ExpiresByType image/svg+xml H0b40000
ExpiresByType image/vnd.microsoft.icon A8640000
ExpiresByType application/vnd.ms-fontobject A8640000
ExpiresByType application/font-sfnt A8640000
ExpiresByType application/font-woff A8640000
</IfModule>

# Output compression
<IfModule mod_deflate.c>
    AddOutputFilterByType DEFLATE application/javascript text/css text/html image/svg+xml
</IfModule>

# Disabling of directory listing
Options All -Indexes
```