

```
# Turn on rewrite engine
RewriteEngine On
RewriteBase /

# Config Environment for Unix
#SetEnv APP_ENV development
#SetEnv ZF2_PATH /var/www/library/Zend2/library
#SetEnv DT2_PATH /var/www/library/Doctrine2

# Config Environment for Windows
SetEnv APP_ENV development
SetEnv ZF2_PATH "F:\ZENDGROUP\SHARE\Library\ZendFramework-2.3.3\library"
SetEnv DT2_PATH "F:\ZENDGROUP\SHARE\Library\Doctrine2"

# The following rule tells Apache that if the requested filename
# exists, simply serve it.
RewriteCond %{REQUEST_FILENAME} -s [OR]
RewriteCond %{REQUEST_FILENAME} -l [OR]
RewriteCond %{REQUEST_FILENAME} -d
RewriteRule ^.*$ - [NC,L]

# The following rewrites all other queries to index.php. The
# condition ensures that if you are using Apache aliases to do
# mass virtual hosting, the base path will be prepended to
# allow proper resolution of the index.php file; it will work
# in non-aliased environments as well, providing a safe, one-size
# fits all solution.
RewriteCond %{REQUEST_URI}::$1 ^(/.+)(.+)$
RewriteRule ^(.*) - [E=BASE:%1]
RewriteRule ^(.*)$ %{ENV:BASE}index.php [NC,L]
```